

## List of Figures

Figure 2-1: Load sharing between single pile and cap ( after Akinmusuru,1980) .....	8
Figure 2-2: Fraction of loads taken by plates and piles for 500mm long piles (after Cao et al., 2004) .....	10
Figure 2-3: Schematic of test setup (after Lee and Chung, 2005).....	11
Figure 2-4: Difference in shaft friction between piles in free standing pile group and piled footing at the settlement of 3 mm or post-yield condition (after Lee and Chung, 2005).....	11
Figure 2-5: Field large-model tests set up: (a) Test on a free-standing pile group; (b) Test on a piled footing with the cap in contact with soil ( after Phuong , 2010).....	15
Figure 2-6 : Load share between cap and individual piles when the sand density and pile length are 38% and 2.3m respectively (after Phuong , 2010) .....	16
Figure 2-7: Schematic view of the experimental apparatus (after El Sawwaf , 2010) .....	16
Figure 2-8 : Variation of average bearing pressures versus maximum settlement for different relative densities of sand (after El Sawwaf , 2010) .....	16
Figure 2-9 : Piled raft configurations in the centrifuge tests (after Giretti, 2010).....	20
Figure 2-10 : Variation of load sharing versus raft relative settlement (settlement of piled raft over raft diameter) (after Giretti, 2010) .....	21
Figure 2-11 : Schematic view of model foundations in the series #2 of centrifuge tests (after Fioravante and Giretti, 2010).....	21
Figure 2-12 : Variation of raft share versus raft relative stiffness for piled raft with different number of piles and slenderness ratios ( after El-Garhy et al., 2013).....	22
Figure 2-13 Load sharing of a piled raft with different number of piles and also various slenderness ratio ( after El-Garhy et al., 2013).....	22
Figure 2-14 : The proposed empirical curves for estimating the load sharing of non-displacement piled raft in homogeneous sand as the function of $W/d_r$ and $S/d_p$ ( after Vakili, 2015) .....	25
Figure 2-15 : Proposed empirical curves for estimating the load sharing of non-displacement piled raft in layered soil when the raft was founded on loose sand, and $S/d_p=3.5$ ( after Vakili, 2015) .....	26
Figure 2-16 : Proposed empirical curves for estimating the load sharing of non-displacement piled raft in layered soil when the raft was founded on loose sand, and $S/d_p=5.2$ ( after Vakili, 2015) .....	26
Figure 2-17 : Proposed empirical curves for estimating the load sharing of non-displacement piled raft in layered soil when the raft was founded on medium sand, and $S/d_p=3.5$ ( after Vakili, 2015).....	27

Figure 2-18 : Proposed curves for estimating the load sharing of non-displacement piled raft in layered soil when the raft was founded on medium sand, and $S/d_p=5.2$ ( after Vakili, 2015) .....	27
Figure 2-19 : Experimental results with $s/d = 6.67$ and $s/d = 3.33$ for 13 piled raft (after Jamil et. Al, 2023) .....	30
Figure 2-20 Numerical results with $s/d = 6.67$ and $s/d = 3.33$ for 13 piled raft (after Jamil et. Al, 2023).....	30
Figure 2-21: Simplified representation of a pile-raft unit (after Poulos, 2001).....	38
Figure 2-22 : Simplified load-settlement curve for preliminary analysis of piled raft foundation (after Poulos, 2001) .....	38
Figure 2-23 : Typical results from MATHCAD analysis: (a) settlement, (b) factor of safety plotted against number of piles (after Poulos, 2001) .....	41
Figure 2-24: Definition of problem for an individual column load (after Poulos, 2001) .....	41
Figure 2-25 : Moment factors A, B for circular column (after Poulos, 2001) .....	42
Figure 2-26 : Shear factor, $cq$ for circular column (after Poulos, 2001).....	43
Figure 2-27 : Contact pressure factor, $q$ (after Poulos, 2001) .....	44
Figure 2-28 : Settlement factor, $\omega$ (soil assumed to be homogeneous and very deep) (after Poulos, 2001).....	45
Figure 2-29 : Burland’s simplified design concept (after Burland, 1995) .....	49
Figure 2-30 : Effect of pile-raft stiffness ratio on the raft efficiency factor, $\alpha_r$ , (after Omeman et al., 2012) .....	51
Figure 2-31: Effect of pile-raft stiffness ratio on the pile efficiency factor, $\alpha_p$ , (after Omeman et al., 2012) .....	51
Figure 2-32 : Procedure for preliminary design of piled-raft foundations (after Omeman et al., 2012) .....	52
Figure 2-33: $\alpha_{p\alpha_{ur}}$ versus $k_{ur}k_{pg}$ for loose, medium, and dense sand (after Alsanabani, 2017) .....	57
Figure 2-34 : Flowchart for the estimation of piled raft settlement (adapted from Bhartiya et al., 2020).....	58
Figure 2-35 : The considered pile raft configuration in 2D analyses (after Omeman, 2012) .	63
Figure 2-36: Variation of raft share versus pile diameter at a constant load for 5 different piled raft configurations (after Omeman, 2012).....	63
Figure 2-37 : The load sharing of single piled raft unit at 600kPa in different slenderness ratio (after Omeman, 2012) .....	64
Figure 2-38 : Influence of pile spacing on load settlement behaviour (after Sinha, 2013).....	65
Figure 2-39 : Variation of load sharing versus pile spacing (after Sinha, 2013).....	66

Figure 2-40 : Sketch of Composite Piled Raft System (after Bhowmik , 2013) .....	67
Figure 2-41 : Various Configuration of piled raft foundation (after Adel et al., 2014).....	68
Figure 2-42 : Soil profile, foundation plan and elevation of nineteen story residential tower (after Yamashita et al., 2011) .....	71
Figure 2-43 : Soil profile, foundation plan and elevation of eleven story base-isolated office building (after Yamashita et al., 2011).....	72
Figure 2-44 : Soil profile, foundation plan and elevation of Hardon experimental hall (after Yamashita et al., 2011).....	73
Figure 2-45 : The soil profile and the foundation plan of 47 story residential tower (after Yamashita et al., 2010).....	74
Figure 2-46 : Variation of vertical displacement versus time (after Yamashita et al., 2010) .	74
Figure 2-47 : Variation of pile share versus pile spacing in piled raft foundation (after Yamashita et al., 2011).....	75
Figure 2-48 : Project Datum Jelatek in KL, Malaysia (after Phung Duc Long, 2016).....	77
Figure 2-49 : Conventional pile foundation layout (after Phung Duc Long, 2016) .....	77
Figure 3-1: Particle Size Distribution Curve of Orsang River Sand and Narmada River Sand (Dry Sieve Analysis Test) .....	87
Figure 3-2 : Microscopic view of sand particles with 10 x magnification.....	87
Figure 4-1 : Model pile.....	92
Figure 4-2 : Connection of central pile with raft .....	92
Figure 4-3 : Model piled raft foundation.....	93
Figure 4-4 : Model pile group.....	93
Figure 4-5 : centering of model piled raft using plumb bob .....	94
Figure 4-6 : Interpretation of load-displacement diagram ( after Moshfeghi and Eslami, 2016) .....	96
Figure 4-7 : Model piles with different $L/d$ ratio of piles.....	97
Figure 4-8 : Schematic diagram of Model piles ( Hollow circular cross section with close end).....	97
Figure 4-9 : Model piles with different shape of piles.....	98
Figure 4-10 : Schematic diagram of cross section of Model piles with different shapes .....	98
Figure 4-11 : Mild steel Plate with different roughness used in direct shear box test to measure the different soil pile friction angle .....	99
Figure 4-12 : Mild steel Plate and model piles with different roughness or soil pile friction angle .....	99

Figure 4-13 : Model raft of piled raft foundation with spacing between piles = $3d$ (Shape of raft = Square; $S=3d$ ; $PG=3 \times 3$ ; All dimensions in mm) .....	102
Figure 4-14 : Model raft of piled raft foundation with spacing between piles = $5d$ (Shape of raft = Square; $S = 5d$ ; $PG = 3 \times 3$ ; All dimensions in mm) .....	103
Figure 4-15 : Model raft of piled raft foundation with spacing between piles = $7d$ (Shape of raft = Square; $S = 7d$ ; $PG = 3 \times 3$ ; All dimensions in mm) .....	104
Figure 4-16 : Model raft of piled raft foundation with different $L/d$ ratio of piles (Shape of raft = Square; $S = 5d$ ; $PG = 3 \times 3$ ; $L/d = 10,20,30$ ; All dimensions in mm) .....	104
Figure 4-17 : Model raft of piled raft foundation with rectangular raft (Shape of raft = rectangular; $S = 7d$ ; $PG = 3 \times 3$ ; $L/d = 30$ ; All dimensions in mm).....	105
Figure 4-18 : Model raft of piled raft foundation with circular raft (Shape of raft = circular; $S = 7d$ ; $PG = 3 \times 3$ ; $L/d = 30$ ; All dimensions in mm).....	105
Figure 4-19 : Model raft of piled raft foundation with square raft (Shape of raft = square; $S = 7d$ ; $PG = 3 \times 3$ ; $L/d = 30$ ; All dimensions in mm).....	106
Figure 4-20 : Model raft of piled raft foundation with trapezoidal raft (Shape of raft = trapezoidal; $S = 7d$ ; $PG = 3 \times 3$ ; $L/d = 30$ ; All dimensions in mm).....	106
Figure 4-21 : Model raft of piled raft foundation with different shape of piles (Shape of raft = square; $S = 5d$ ; $PG = 3 \times 3$ ; $L = 300$ mm; All dimensions in mm) .....	107
Figure 4-22 : Model piled raft for the study of configuration of piles (All dimensions are in mm) .....	108
Figure 4-23 : Configuration of pile with varying length of piles and position of pile.....	109
Figure 4-24 : Experimental set-up .....	110
Figure 4-25 : Surface vibrator.....	111
Figure 4-26 : Galvanized steel boxes.....	111
Figure 4-27 : Arrangement of density box between piles .....	111
Figure 4-28 : Compaction frame.....	112
Figure 4-29 : Mild steel compaction frame for compacting the soil between the piles.....	112
Figure 4-30 : Removal of compaction frame after compacting the soil between the piles at topmost layer .....	112
Figure 4-31 : Removal of raft and compaction frame after compacting the soil between the piles at topmost layer .....	112
Figure 4-32 : Reconnection of raft with piles.....	112
Figure 4-33 : Earth pressure cells .....	113
Figure 4-34 : Indicator of earth pressure cells and strain gauges .....	113
Figure 4-35 : Marking at every 5 cm height on inner side of tank .....	114

Figure 4-36 : Arrangement of boxes for the determination of densities .....	114
Figure 4-37 : Experimental setup for load test on pile group.....	117
Figure 4-38 : Experimental setup for load test on piled raft .....	117
Figure 4-39 : Output of the numerical analysis .....	120
Figure 4-40 : Messe - Torhas Building .....	123
Figure 4-41 : Validation of the present numerical model with numerical results reported by Engine et.al (2009).....	123
Figure 4-42 : Comparison of Load –settlement characteristic obtained from present study with Ahmed et al. (2021).....	126
Figure 4-43 : Piled raft profile (after ANDRÉ RYLTEINIUS).....	127
Figure 4-44 : Total displacement for the study.....	128
Figure 4-45 : comparison of load settlement characteristics of model piled raft from experimental and numerical study ( <i>Square piled raft with 9 piles in Square group: L/d ratio of pile = 30; spacing between piles = 7d; <math>I_d = 60\%</math></i> ) .....	129
Figure 4-46 : comparison of load settlement characteristics of model piled raft from experimental and numerical study ( <i>Square piled raft with 25 piles in Square group: L/d ratio of pile = 20; spacing between piles = 5d; <math>I_d = 60\%</math></i> ) .....	129
Figure 4-47 : Various Configuration of pile in square pattern (S1 – S9) and circular pattern (C1- C9).....	132
Figure 4-48 : Load considered in the large piled raft.....	132
Figure 5-1 Load settlement curve of unpiled raft foundation to define Initial Tangent stiffness of Unpiled raft UPR( $k_{ri}$ ) and Secant stiffness of Unpiled raft UPR ( $k_{sr}$ ) .....	134
Figure 5-2 : Load-settlement characteristics of model piled raft foundation with trapezoidal raft at $I_d = 40\%$ .....	136
Figure 5-3 : Tri- linear Load-settlement characteristics of model piled raft foundation (MPRF) with trapezoidal raft at $I_d = 40\%$ .....	136
Figure 5-4 : Tri- linear Load-settlement characteristics of model piled raft foundation (MPRF), unpiled raft (UPR) with trapezoidal raft and single pile at $I_d = 40\%$ .....	136
Figure 5-5 : Location of EPC and piles in model piled raft foundation (Not to scale, All dimensions are in mm) .....	139
Figure 5-6 : Location of instrumented piles in MPRF .....	140
Figure 5-7 : Location of strain gauges in instrumented pile.....	140
Figure 5-8 : Load settlement characteristics of unpiled raft foundation with different shape of raft ( $I_d = 40\%$ ).....	143
Figure 5-9 : Load settlement characteristics of unpiled raft foundation with different shape of raft ( $I_d = 60\%$ ).....	143

Figure 5-10 : Load settlement characteristics of unpiled raft foundation with different shape of raft ( $I_d = 80\%$ ).....	143
Figure 5-11 : Load settlement characteristics of unpiled raft foundation with square raft ( $I_d = 40\%$ , $60\%$ and $80\%$ ; size of raft = $240\text{mm} \times 240\text{mm}$ ).....	143
Figure 5-12 : Comparison of load settlement characteristics of square shaped unpiled raft foundation obtained from experimental study and PLAXIS 3D software .....	144
Figure 5-13 : Ultimate load of unpiled raft foundation ( $Q_{ur}$ ) with different shape of raft and at different relative densities of sand bed.....	145
Figure 5-14 : Secant stiffness of square shaped unpiled raft from experimental study and proposed equation ( $I_d = 40\%$ , $60\%$ and $80\%$ ; size of raft = $220\text{ mm} \times 220\text{ mm}$ ) .....	149
Figure 5-15 : Secant stiffness of circular shaped unpiled raft from experimental study and proposed equation ( $I_d = 40\%$ , $60\%$ and $80\%$ ; diameter of raft = $248.3\text{ mm}$ ) .....	150
Figure 5-16 : comparison of Load calculated from EPC readings and actual applied load vs. relative settlement of unpiled raft foundation ( <i>Square raft</i> , $I_d = 60\%$ ) .....	151
Figure 5-17 : Load settlement characteristics of single pile with different $L/d$ ratio in sand ( $I_d = 40\%$ ; $d = 9.7\text{ mm}$ ).....	152
Figure 5-18 : Load settlement characteristics of single pile with different $L/d$ ratio in sand ( $I_d = 60\%$ ; $d = 9.7\text{ mm}$ ).....	152
Figure 5-19 : Load settlement characteristics of single pile with different $L/d$ ratio in sand ( $I_d = 80\%$ ; $d = 9.7\text{ mm}$ ).....	153
Figure 5-20 : Load settlement characteristics of pile group with different spacing between piles in sand ( $L/d$ ratio of pile= $30$ ; $I_d = 40\%$ ; $d = 9.7\text{ mm}$ ; <i>Square uare pile group with <math>3 \times 3</math> pile arrangement</i> ).....	153
Figure 5-21: Load settlement characteristics of pile group with different spacing between piles in sand ( $L/d$ ratio of pile = $30$ ; $I_d = 60\%$ ; $d = 9.7\text{ mm}$ ; <i>Square pile group with <math>3 \times 3</math> pile arrangement</i> ) .....	153
Figure 5-22 : Load settlement characteristics of pile group with different spacing between piles in sand ( $L/d$ ratio of pile = $30$ ; $I_d = 80\%$ ; $d = 9.7\text{ mm}$ ; <i>Square pile group with <math>3 \times 3</math> pile arrangement</i> ) .....	153
Figure 5-23 : Load settlement characteristics of pile group with different $L/d$ ratio of piles in sand ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7\text{ mm}$ ; <i>pile group = <math>5 \times 5</math></i> ).....	155
Figure 5-24 : Load settlement characteristics of pile group with $L/d$ ratio of piles in sand ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7\text{ mm}$ ; <i>pile group = <math>5 \times 5</math></i> ) .....	155
Figure 5-25 : Load settlement characteristics of pile group with different $L/d$ ratio of piles in sand ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7\text{ mm}$ ; <i>pile group = <math>5 \times 5</math></i> ).....	155
Figure 5-26 : Load settlement characteristics of pile group with different shape of piles in sand ( $S = 5d$ ; $I_d = 40\%$ ; <i>pile group = <math>3 \times 3</math></i> ).....	157

Figure 5-27 : Load settlement characteristics of pile group with different shape of piles in sand ( $S = 5d$ ; $I_d = 60\%$ ; <i>pile group</i> = $3 \times 3$ ).....	157
Figure 5-28 : Load settlement characteristics of pile group with different shape of piles in sand ( $S = 5d$ ; $I_d = 80\%$ ; <i>pile group</i> = $3 \times 3$ ).....	157
Figure 5-29 : Load settlement characteristics of model circular piled raft at different relative density of sand bed ( $S = 7d$ ; <i>pile group</i> = $3 \times 3$ ) .....	165
Figure 5-30 : Load settlement characteristics of model rectangular piled raft at different relative density of sand bed ( $S = 7d$ ; <i>pile group</i> = $3 \times 3$ ).....	165
Figure 5-31 : Load settlement characteristics of model trapezoidal piled raft at different relative density of sand bed ( $S = 7d$ ; <i>pile group</i> = $3 \times 3$ ).....	166
Figure 5-32 : Load settlement characteristics of model square piled raft at different relative density of sand bed ( $S = 7d$ ; <i>pile group</i> = $3 \times 3$ ) .....	166
Figure 5-33 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with circular shape of raft at different relative density of sand ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ).....	167
Figure 5-34 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with rectangular shape of raft at different relative density of sand ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ).....	167
Figure 5-35 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with trapezoidal shape of raft at different relative density of sand ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ).....	167
Figure 5-36 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with square shape of raft at different relative density of sand ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ).....	167
Figure 5-37 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ; <i>shape of raft</i> = <i>circular</i> ) .....	168
Figure 5-38 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ; <i>shape of raft</i> = <i>rectangular</i> ) .....	168
Figure 5-39 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ; <i>shape of raft</i> = <i>trapezoidal</i> ) .....	168
Figure 5-40 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; <i>pile group</i> = $3 \times 3$ ; <i>shape of raft</i> = <i>square</i> ) .....	168
Figure 5-41 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ; <i>shape of raft</i> = <i>circular</i> ) ...	171

Figure 5-42 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ; *shape of raft = circular*) ... 171

Figure 5-43 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ; *shape of raft = circular*) ... 172

Figure 5-44 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 40\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = circular*) ..... 172

Figure 5-45 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 60\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = circular*) ..... 172

Figure 5-46 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 80\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = circular*) ..... 172

Figure 5-47 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ; *shape of raft = rectangular*) ..... 173

Figure 5-48 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ; *shape of raft = rectangular*) ..... 173

Figure 5-49 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ; *shape of raft = rectangular*) ..... 174

Figure 5-50 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 40\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = rectangular*) ..... 174

Figure 5-51 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 60\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = rectangular*) ..... 174

Figure 5-52 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 80\%$ ;  $S = 7d$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm; *pile group = 3 × 3; shape of raft = rectangular*) ..... 174

Figure 5-53 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ; *shape of raft = trapezoidal*) ..... 175

Figure 5-54 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ; *shape of raft = trapezoidal*) ..... 175

Figure 5-55 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ; <i>shape of raft = trapezoidal</i> ) .....	176
Figure 5-56 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 40\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = trapezoidal</i> ) .....	176
Figure 5-57 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 60\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = trapezoidal</i> ) .....	176
Figure 5-58 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 80\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = trapezoidal</i> ) .....	176
Figure 5-59 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ; <i>shape of raft = square</i> ) .....	177
Figure 5-60 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ; <i>shape of raft = square</i> ) .....	177
Figure 5-61 : Contact pressure distribution below unpiled raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ; <i>shape of raft = square</i> ) .....	178
Figure 5-62 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 40\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = square</i> ) .....	178
Figure 5-63 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 60\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = square</i> ) .....	178
Figure 5-64 : Contact pressure distribution below raft for different location of earth pressure cells in PRF vs. relative settlement characteristics ( $I_d = 80\%$ ; $S = 7d$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = square</i> ) .....	178
Figure 5-65 : Load settlement characteristics of piled raft and load shared by pile group and raft at different relative densities of sand ( $S = 7d$ ; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = circular</i> ) .....	179
Figure 5-66 : Load settlement characteristics of piled raft and load shared by pile group and raft at different relative densities of sand ( $S = 7d$ ; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = rectangular</i> ) .....	179
Figure 5-67 : Load settlement characteristics of piled raft and load shared by pile group and raft at different relative densities of sand ( $S = 7d$ ; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = trapezoidal</i> ) .....	180
Figure 5-68 : Load settlement characteristics of piled raft and Load sharing by pile group and raft at different relative densities of sand ( $S = 7d$ ; $d = 9.7$ mm; <i>pile group = 3 × 3</i> ; <i>shape of raft = square</i> ) .....	180

Figure 5-69 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in circular piled raft vs. relative settlement at 40% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	181
Figure 5-70 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in circular piled raft vs. relative settlement at 60% relative density of sand bed ( $S=7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	181
Figure 5-71 : Percentage load shared by pile group(% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in circular piled raft vs. relative settlement at 80% relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	181
Figure 5-72 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in rectangular piled raft vs. relative settlement at 40% relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	181
Figure 5-73 : Percentage load shared by pile group(% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in rectangular piled raft vs. relative settlement at 60% relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	182
Figure 5-74 : Percentage load shared by pile group(% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in rectangular piled raft vs. relative settlement at 80% relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	182
Figure 5-75 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in trapezoidal piled raft vs. relative settlement at 40% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	183
Figure 5-76 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in trapezoidal piled raft vs. relative settlement at 60% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	183
Figure 5-77 : Percentage load shared by pile group ( % <i>LSPG</i> ) and raft ( % <i>LSR</i> ) in trapezoidal piled raft vs. relative settlement at 80% relative density of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	184
Figure 5-78 : Percentage load shared by pile group ( % <i>LSPG</i> ) and raft ( % <i>LSR</i> ) in square piled raft vs. relative settlement at 40% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	184
Figure 5-79 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in square piled raft vs. relative settlement at 60% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	185
Figure 5-80 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in square piled raft vs. relative settlement at 80% relative density of sand bed ( $S = 7d$ ; $d = 9.7\text{mm}$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	185
Figure 5-81 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = circular) .....	188

Figure 5-82 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = circular).....	188
Figure 5-83 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = rectangular) .....	188
Figure 5-84 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = rectangular) .....	188
Figure 5-85 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = trapezoidal) .....	189
Figure 5-86 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = trapezoidal) .....	189
Figure 5-87 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = square) .....	189
Figure 5-88 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for configuration of piles at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = square) .....	189
Figure 5-89 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = Circular) .....	191
Figure 5-90 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = Rectangular) .....	191
Figure 5-91 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = Trapezoidal).....	191
Figure 5-92 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; shape of raft = Square) .....	191
Figure 5-93 : Comparison of <i>IYL</i> of piled raft foundation with different shape of raft at different relative density of sand bed found from experimental results and calculated from proposed equation .....	209
Figure 5-94 : Comparison of <i>FYL</i> of piled raft foundation with different shape of raft at different relative density of sand bed found from experimental results and calculated from proposed equation .....	211

Figure 5-95 : Comparison of primary stiffness of PRF $k_{prp}$ (experimental) and determined from proposed equation.....	215
Figure 5-96 : Comparison of primary stiffness of PRF $k_{prs}$ (experimental) and determined from proposed equation.....	217
Figure 5-97 : Load settlement characteristics of model piled raft with different $L/d$ ratio of piles ( $S = 5d$ ; $pile\ group = 5 \times 5$ ; $I_d = 40\%$ ).....	222
Figure 5-98 : Load settlement characteristics of model piled raft with different $L/d$ ratio of piles ( $S = 5d$ ; $pile\ group = 5 \times 5$ ; $I_d = 60\%$ ).....	222
Figure 5-99 : Load settlement characteristics of model piled raft with different $L/d$ ratio of piles ( $S = 5d$ ; $pile\ group = 5 \times 5$ ; $I_d = 80\%$ ).....	223
Figure 5-100 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 10; $I_d = 40\%$ , 60%, and 80%; $pile\ group = 5 \times 5$ ).....	223
Figure 5-101 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 5d$ ; $I_d = 40\%$ , 60%, and 80%; $L/d$ ratio of pile = 20; $pile\ group = 5 \times 5$ ).....	224
Figure 5-102 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 5d$ ; $I_d = 40\%$ , 60%, and 80%; $L/d$ ratio of pile = 30; $pile\ group = 5 \times 5$ ).....	224
Figure5-103 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with $L/d$ ratio of pile = 10 ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ) .....	227
Figure 5-104 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with $L/d$ ratio of pile = 20 ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ) .....	227
Figure 5-105 : Load settlement characteristics of only pile group, unpiled raft, and piled raft with $L/d$ ratio of pile = 30 ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ) .....	227
Figure 5-106 : Load settlement characteristics of piled raft and Load shared by pile group and raft at different relative densities of sand ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ; $L/d$ ratio = 10).....	228
Figure 5-107 : Load settlement characteristics of piled raft and Load shared by pile group and raft at different relative densities of sand ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ; $L/d$ ratio = 20).....	228
Figure 5-108 : Load settlement characteristics of piled raft and Load shared by pile group and raft at different relative densities of sand ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ; $L/d$ ratio = 30).....	229
Figure5-109 : Load settlement characteristics of piled raft and Load shared by pile group and raft in PRF with different $L/d$ ratios of pile at 40% relative density of sand ( $S = 5d$ ; $d = 9.7\ mm$ ; $pile\ group = 5 \times 5$ ) .....	229

Figure 5-110 : Load settlement characteristics of piled raft and Load shared by pile group and raft in PRF with different $L/d$ ratios of pile at 60% relative density of sand ( $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ) .....	230
Figure 5-111 : Load settlement characteristics of piled raft and Load shared by pile group and raft in PRF with different $L/d$ ratios of pile at 80% relative density of sand ( $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ) .....	230
Figure 5-112 : Percentage load shared by pile group (%LSPG) and raft (%LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 10) .....	231
Figure 5-113 : Percentage load shared by pile group (%LSPG) and raft (%LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 20) .....	231
Figure 5-114 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 30).....	232
Figure 5-115 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 10).....	232
Figure 5-116 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 20).....	232
Figure 5-117 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 30).....	232
Figure 5-118 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 10).....	233
Figure 5-119 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 20).....	233
Figure 5-120 : Percentage load shared by pile group (% LSPG) and raft (% LSR) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio = 30).....	234
Figure 5-121 : Load shared by pile group and raft at IYL of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile =10; Pile group = $5 \times 5$ ).....	235
Figure 5-122 : Load shared by pile group and raft at FYL of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile =10; Pile group = $5 \times 5$ ).....	235
Figure 5-123 : Load shared by pile group and raft at IYL of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile = 20; Pile group = $5 \times 5$ ).....	236

Figure 5-124 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile = 20; Pile group = $5 \times 5$ ).....	236
Figure 5-125 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile = 30; Pile group = $5 \times 5$ ).....	237
Figure 5-126 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation ( $S = 5d$ ; $L/d$ ratio of pile = 30; Pile group = $5 \times 5$ ).....	237
Figure 5-127 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 10; Pile group = $5 \times 5$ ).....	239
Figure 5-128 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 20; Pile group = $5 \times 5$ ).....	239
Figure 5-129 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; Pile group = $5 \times 5$ ).....	239
Figure 5-130 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different $L/d$ ratio of pile ( $S = 5d$ ; $I_d = 40\%$ ; $L/d$ ratio of pile = 10, 20 and 30; Pile group = $5 \times 5$ ) .....	239
Figure 5-131 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different $L/d$ ratio of pile ( $S = 5d$ ; $I_d = 60\%$ ; $L/d$ ratio of pile = 10, 20 and 30; Pile group = $5 \times 5$ ) .....	240
Figure 5-132 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different $L/d$ ratio of pile ( $S = 5d$ ; $I_d = 80\%$ ; $L/d$ ratio of pile = 10, 20 and 30; Pile group = $5 \times 5$ ) .....	240
Figure 5-133 : Comparison of <i>IYL</i> of piled raft foundation with different $L/d$ ratios of pile at different relative density of sand bed found from experimental results and calculated from proposed equation .....	247
Figure 5-134 : Comparison of <i>FYL</i> of piled raft foundation with different $L/d$ ratios of pile at different relative density of sand bed found from experimental results and calculated from proposed equation .....	249
Figure 5-135 : Comparison of primary stiffness of PRF ( $k_{pr}$ ) <sub>p</sub> with different $L/d$ ratios of pile (experimental) and determined from the proposed equation.....	252
Figure 5-136 : Comparison of secondary stiffness of PRF $k_{pr}$ with different $L/d$ ratios of pile (experimental) and determined from the proposed equation.....	254
Figure 5-137 : Load settlement characteristics of model square piled raft at different relative density of sand bed ( $S = 3d$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm) .....	256
Figure 5-138 : Load settlement characteristics of model square piled raft at different relative density of sand bed ( $S = 5d$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $d = 9.7$ mm) .....	256

Figure 5-139 : Load settlement characteristics of model square piled raft at different relative density of sand bed ( $S = 7d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 256

Figure 5-140 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 3d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm)..... 256

Figure 5-141 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 5d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm)..... 257

Figure 5-142 : Initial yield load ( $IYL$ ) and Final yield load ( $FYL$ ) of piled raft foundation at different relative density of sand bed ( $S = 7d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm)..... 257

Figure 5-143 : Load settlement characteristics of only pile group, unpiled raft, and piled raft at different relative density of sand bed ( $S = 3d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 258

Figure 5-144 : Load settlement characteristics of only pile group, unpiled raft, and piled raft at different relative density of sand bed ( $S = 5d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 258

Figure 5-145 : Load settlement characteristics of only pile group, unpiled raft, and piled raft at different relative density of sand bed ( $S = 7d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 258

Figure 5-146 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ;  $S = 3d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 258

Figure 5-147: Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ;  $S = 3d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 260

Figure 5-148 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ;  $S = 3d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 260

Figure 5-149 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ;  $S = 5d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 260

Figure 5-150 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ;  $S = 5d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 260

Figure 5-151 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ;  $S = 5d$ ; pile group =  $3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 261

Figure 5-152 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 40\%$ ;  $S = 7d$ ;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 261

Figure 5-153 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 60\%$ ;  $S = 7d$ ;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 261

Figure 5-154 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $I_d = 80\%$ ;  $S = 7d$ ;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio of pile = 30;  $d = 9.7$  mm) ..... 261

Figure 5-155 : Load settlement characteristics of piled raft and Load sharing by pile group and raft at different relative densities of sand ( $S = 3d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 262

Figure 5-156 : Load settlement characteristics of piled raft and Load sharing by pile group and raft at different relative densities of sand ( $S = 5d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 262

Figure 5-157 : Load settlement characteristics of piled raft and Load sharing by pile group and raft at different relative densities of sand ( $S=7d$ ;  $d=9.7$ mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 263

Figure 5-158 : Load shared by pile group and raft at *IYL* of piled raft foundation ( $S = 3d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 266

Figure 5-159 : Load shared by pile group and raft at *FYL* of piled raft foundation ( $S = 3d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 266

Figure 5-160 : Load shared by pile group and raft at *IYL* of piled raft foundation ( $S = 5d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 267

Figure 5-161 : Load shared by pile group and raft at *FYL* of piled raft foundation ( $S = 5d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 267

Figure 5-162 : Load shared by pile group and raft at *IYL* of piled raft foundation ( $S = 7d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 267

Figure 5-163 : Load shared by pile group and raft at *FYL* of piled raft foundation ( $S = 7d$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 267

Figure 5-164 : Percentage load shared by pile group (% *LSPG*) and raft (% *LSR*) in piled raft at different relative settlement ( $S = 3d$ ;  $I_d = 40\%$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 268

Figure 5-165 : Percentage load shared by pile group (% *LSPG*) and raft (% *LSR*) in piled raft at different relative settlement ( $S = 3d$ ;  $I_d = 60\%$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 268

Figure 5-166 : Percentage load shared by pile group (% *LSPG*) and raft (% *LSR*) in piled raft at different relative settlement ( $S = 3d$ ;  $I_d = 80\%$ ;  $d = 9.7$  mm;  $\text{pile group} = 3 \times 3$ ;  $L/d$  ratio = 30) ..... 269

Figure 5-167 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	269
Figure 5-168 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	269
Figure 5-169 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	269
Figure 5-170 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 7d$ ; $I_d = 40\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	270
Figure 5-171 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 7d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	270
Figure 5-172 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 7d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio = 30).....	271
Figure 5-173 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 3d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30).....	271
Figure 5-174 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 5d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30).....	271
Figure 5-175 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different relative densities of sand bed ( $S = 7d$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30).....	271
Figure 5-176 : Comparison of <i>IYL</i> of piled raft foundation with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	280
Figure 5-177 : Comparison of <i>FYL</i> of piled raft foundation with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	282
Figure 5-178 : Comparison of primary stiffness of PRF <i>kprp</i> with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	285
Figure 5-179 : Comparison of secondary stiffness of PRF <i>kprs</i> with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	287

Figure 5-180 : Load settlement characteristics of piled raft foundation with different configurations of piles ( $L/d$ ratio of pile =10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; CF-1 to CF-3) .....	288
Figure 5-181 : Load settlement characteristics of piled raft foundation with different configurations of piles ( $L/d$ ratio of pile =10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; CF-4 to CF-6) .....	288
Figure 5-182 : Load settlement characteristics of piled raft foundation with different configurations of piles ( $L/d$ ratio of pile =10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; CF-7 to CF-9) .....	289
Figure 5-183 : Initial yield load (IYL) and Final yield load (FYL) of piled raft foundation with different pile configurations ( $L/d$ ratio of pile =10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; CF-1 to CF-9).....	289
Figure 5-184 : Load settlement characteristics of piled raft foundation with different configurations of piles ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ).....	290
Figure 5-185 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-1) .....	290
Figure 5-186 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-2) .....	290
Figure 5-187 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-3) .....	290
Figure 5-188 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-4) .....	291
Figure 5-189 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-5) .....	291
Figure 5-190 : Contact pressure distribution below raft for different location of earth pressure cells vs. relative settlement characteristics ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; configuration of piles = CF-6) .....	291
Figure 5-191 : Load settlement characteristics of piled raft and Load sharing by pile group and raft with different configuration of piles ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm ; Pile group = $5 \times 5$ ; configuration of piles = CF-1, CF-2, CF-3).....	292
Figure 5-192 : Load settlement characteristics of piled raft and Load sharing by pile group and raft with different configuration of piles ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm ; Pile group = $5 \times 5$ ; configuration of piles = CF-4, CF-5, CF-6).....	292

Figure 5-193 : Load settlement characteristics of piled raft and Load shared by pile group and raft with different configuration of piles ( $L/d$ ratio of pile = 10, 20, and 30; $I_d = 60\%$ ; $S = 5d$ ; $d = 9.7$ mm ; Pile group = $5 \times 5$ ; configuration of piles = CF-7, CF-8, CF-9) .....	293
Figure 5-194 : Load shared by pile group and raft at $IYL$ of piled raft foundation for configuration of piles at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 10, 20, and 30; configuration of piles = CF-1 to CF-9; pile group = $5 \times 5$ )` .....	294
Figure 5-195 : Load shared by pile group and raft at $FYL$ of piled raft foundation for configuration of piles at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 10, 20, and 30; configuration of piles = CF-1 to CF-9; pile group = $5 \times 5$ ) .....	295
Figure 5-196 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10, 20 and 30; CF-1) .....	296
Figure 5-197 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10, 20 and 30; CF-2) .....	296
Figure 5-198 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10 and 30; CF-3) .....	296
Figure 5-199 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10 and 30; CF-4) .....	296
Figure 5-200 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10, 20 and 30; CF-5) .....	297
Figure 5-201 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10, 20 and 30; CF-6) .....	297
Figure 5-202 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 10; CF-7).....	297
Figure 5-203 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 20; CF-8).....	297
Figure 5-204 : Percentage load shared by pile group (% $LSPG$ ) and raft (% $LSR$ ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 30; CF-9).....	298
Figure 5-205 : Piled raft coefficient ( $\alpha p$ ) vs. relative settlement characteristics of piled raft foundation at different configuration of piles ( $I_d = 60\%$ ; $S = 5d$ ; $L/d$ ratio of pile = 30; configuration of piles = CF-1 to CF-9; pile group = $5 \times 5$ ).....	299

Figure 5-206 : Comparison of <i>IYL</i> of piled raft foundation with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	306
Figure 5-207 : Comparison of <i>FYL</i> of piled raft foundation with different spacing between piles at different relative density of sand bed found from experimental results and calculated from proposed equation.....	309
Figure 5-208 : Load settlement characteristics of piled raft foundation with different soil pile friction in sand ( $L/d$ ratio of pile = 30; $I_d = 40\%$ ; $d = 9.7$ mm) .....	310
Figure 5-209 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_0 = 22.4^\circ$ at 40% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	310
Figure 5-210 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_1 = 24.36^\circ$ at 40% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	311
Figure 5-211 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_2 = 25.8^\circ$ at 40% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	311
Figure 5-212 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_3 = 27.1^\circ$ at 40% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	312
Figure 5-213 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different soil pile friction angles ( $S = 5d$ ; $I_d = 40\%$ ; $L/d$ ratio of pile = 30) .....	312
Figure 5-214 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for different soil pile friction angle at 40% relative density of sand bed ( $S = 5d$ ; $I_d = 40\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	313
Figure 5-215 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for different soil pile friction angle at 40% relative density of sand bed ( $S = 5d$ ; $I_d = 40\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	313
Figure 5-216 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 30; $\delta_0 = 22.5^\circ$ ).....	314
Figure 5-217 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 30; $\delta_1 = 24.36^\circ$ ).....	314
Figure 5-218 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7$ mm; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 30; $\delta_2 = 25.8^\circ$ ).....	314

Figure 5-219 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 40\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $5 \times 5$ ; $L/d$ ratio of pile = 30; $\delta_3 = 27.1^\circ$ ).....	314
Figure 5-220 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different soil pile friction ( $S = 5d$ ; $I_d = 40\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	315
Figure 5-221 : Load settlement characteristics of piled raft foundation with different soil pile friction in sand ( $L/d$ ratio of pile = 30; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ).....	316
Figure 5-222 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_0 = 24.5^\circ$ at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ).....	316
Figure 5-223 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_1 = 25.7^\circ$ at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ).....	317
Figure 5-224 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_2 = 26.58^\circ$ at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ).....	317
Figure 5-225 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_3 = 27.1^\circ$ at 60% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ).....	317
Figure 5-226 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different soil pile friction angles ( $S = 5d$ ; $I_d = 60\%$ ; $L/d$ ratio of pile = 30).....	317
Figure 5-227 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for different soil pile friction angle at 60% relative density of sand bed ( $S = 5d$ ; $I_d = 60\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	319
Figure 5-228 Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for different soil pile friction angle at 60% relative density of sand bed ( $S = 5d$ ; $I_d = 60\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	319
Figure 5-229 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_0 = 24.5^\circ$ ).....	320
Figure 5-230 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_1 = 25.7^\circ$ ).....	320
Figure 5-231 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_2 = 26.58^\circ$ ).....	320

Figure 5-232 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 60\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_3 = 26.58^\circ$ ).....	320
Figure 5-233 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different soil pile friction ( $S = 5d$ ; $I_d = 60\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	321
Figure 5-234 : Load settlement characteristics of piled raft foundation with different soil pile friction in sand ( $L/d$ ratio of pile = 30; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ) .....	322
Figure 5-235 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_0 = 26.3^\circ$ at 80% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	322
Figure 5-236 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_1 = 27.41^\circ$ at 80% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	323
Figure 5-237 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_2 = 28.22^\circ$ at 80% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	323
Figure 5-238 : Load settlement characteristics of piled raft and Load shared by pile group and raft with soil pile friction angle $\delta_3 = 30.04^\circ$ at 80% relative density of sand bed ( $S = 5d$ ; $L/d$ ratio of pile = 30; pile group = $3 \times 3$ ) .....	324
Figure 5-239 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation at different soil pile friction angles ( $S = 5d$ ; $I_d = 80\%$ ; $L/d$ ratio of pile = 30) .....	324
Figure 5-240 : Load shared by pile group and raft at <i>IYL</i> of piled raft foundation for different soil pile friction angle at 80% relative density of sand bed ( $S = 5d$ ; $I_d = 80\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	325
Figure 5-241 : Load shared by pile group and raft at <i>FYL</i> of piled raft foundation for different soil pile friction angle at 80% relative density of sand bed ( $S = 5d$ ; $I_d = 80\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	325
Figure 5-242 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_0 = 26.3^\circ$ ).....	326
Figure 5-243 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_1 = 27.41^\circ$ ).....	326
Figure 5-244 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_2 = 28.22^\circ$ ).....	326

Figure 5-245 : Percentage load shared by pile group (% <i>LSPG</i> ) and raft (% <i>LSR</i> ) in piled raft at different relative settlement ( $S = 5d$ ; $I_d = 80\%$ ; $d = 9.7 \text{ mm}$ ; pile group = $3 \times 3$ ; $L/d$ ratio of pile = 30; $\delta_3 = 30.04^\circ$ ).....	326
Figure 5-246 : Piled raft coefficient ( $\alpha_p$ ) vs. relative settlement characteristics of piled raft foundation at different soil pile friction ( $S = 5d$ ; $I_d = 80\%$ ; $L/d$ ratio of pile = 30; Pile group = $3 \times 3$ ).....	327
Figure 5-247 : Load settlement characteristics of model square piled raft with different shape of piles at 40% relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm) .....	335
Figure 5-248 : Load settlement characteristics of model square piled raft with different shape of piles at 60% relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm) .....	335
Figure 5-249 : Load settlement characteristics of model square piled raft with different shape of piles at 80% relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm) .....	336
Figure 5-250 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation with H pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	336
Figure 5-251 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation with HC pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	336
Figure 5-252 : Initial yield load ( <i>IYL</i> ) and Final yield load ( <i>FYL</i> ) of piled raft foundation with HSQ pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	336
Figure 5-253 : Load settlement characteristics of only pile group, unpiled raft, and piled raft foundation with H pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	338
Figure 5-254 : Load settlement characteristics of only pile group, unpiled raft, and piled raft foundation with HC pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	338
Figure 5-255 : Load settlement characteristics of only pile group, unpiled raft, and piled raft foundation with HSQ pile at different relative density of sand bed ( $S = 5d$ ; $d = 16 \text{ mm}$ ; pile group = $3 \times 3$ ; $L$ of pile = 300 mm).....	338
Figure 5-256 Load settlement curve for all configuration pile.....	347
Figure 5-257 : Load settlement curve for all configurations of pile in square pattern .....	348
Figure 5-258 : Load settlement curve for all configurations of pile in circular pattern.....	348
Figure 5-259 : Tri-linear load settlement behaviour of PRF for $S1$ , $S2$ and $S3$ .....	349
Figure 5-260 : Tri-linear load settlement behaviour of PRF for $S3$ , $S4$ and $S5$ .....	349

Figure 5-261 : Tri-linear load settlement behaviour of PRF for <i>S7</i> , <i>S8</i> and <i>S9</i> .....	349
Figure 5-262 : Tri-linear load settlement behaviour of PRF for <i>C1</i> , <i>C2</i> and <i>C3</i> .....	349
Figure 5-263 : Tri-linear load settlement behaviour of PRF for <i>C4</i> , <i>C5</i> and <i>C6</i> .....	350
Figure 5-264 : Tri-linear load settlement behaviour of PRF for <i>C7</i> , <i>C8</i> and <i>C9</i> .....	350
Figure 5-265 : <i>IYL</i> and <i>FYL</i> for square and circular pattern of piles in Piled-Raft Foundation .....	350
Figure 5-266 : Settlement reduction ratio for all configuration of pile in a Piled-Raft Foundation.....	352
Figure 5-267 : Load Sharing between Pile and Raft at <i>IYL</i> .....	353
Figure 5-268 : Load Sharing between Pile and Raft at <i>FYL</i> .....	353
Figure 5-269 Stressed Zone at Lower Load ( $P=84000$ kN in <i>S8</i> Configuration) .....	354
Figure 5-270 Stressed Zone at Higher Load ( $P=204000$ kN in <i>S8</i> Configuration).....	354
Figure 5-271 : Load Distribution between piles at <i>IYL</i> in <i>S1</i> configuration .....	357
Figure 5-272 : Load Distribution between piles at <i>FYL</i> in <i>S1</i> configuration .....	357
Figure 5-273 : Load Distribution between piles at <i>IYL</i> in <i>S2</i> configuration .....	358
Figure 5-274 : Load Distribution between piles at <i>FYL</i> in <i>S2</i> configuration .....	358
Figure 5-275 : Load Distribution between piles at <i>IYL</i> in <i>S3</i> configuration .....	359
Figure 5-276 : Load Distribution between piles at <i>FYL</i> in <i>S3</i> configuration .....	359
Figure 5-277 : Load Distribution between piles at <i>IYL</i> in <i>S4</i> configuration .....	359
Figure 5-278 : Load Distribution between piles at <i>FYL</i> in <i>S4</i> configuration .....	359
Figure 5-279 : Load Distribution between piles at <i>IYL</i> in <i>S5</i> configuration .....	360
Figure 5-280 : Load Distribution between piles at <i>FYL</i> in <i>S5</i> configuration .....	360
Figure 5-281 : Load Distribution between piles at <i>IYL</i> in <i>S6</i> configuration .....	360
Figure 5-282 : Load Distribution between piles at <i>FYL</i> in <i>S6</i> configuration .....	360
Figure 5-283 : Load Distribution between piles at <i>IYL</i> in <i>S7</i> configuration .....	361
Figure 5-284 : Load Distribution between piles at <i>FYL</i> in <i>S7</i> configuration .....	361
Figure 5-285 : Load Distribution between piles at <i>IYL</i> in <i>S8</i> configuration .....	362
Figure 5-286 : Load Distribution between piles at <i>FYL</i> in <i>S8</i> configuration .....	362
Figure 5-287 : Load Distribution between piles at <i>IYL</i> in <i>S9</i> configuration .....	362
Figure 5-288 : Load Distribution between piles at <i>FYL</i> in <i>S9</i> configuration .....	362
Figure 5-289 : Load Distribution between piles at <i>IYL</i> in <i>C1</i> configuration.....	363
Figure 5-290 : Load Distribution between piles at <i>FYL</i> in <i>C1</i> configuration.....	363
Figure 5-291 : Load Distribution between piles at <i>IYL</i> in <i>C2</i> configuration.....	364

Figure 5-292 : Load Distribution between piles at <i>FYL</i> in <i>C2</i> configuration.....	364
Figure 5-293 : Load Distribution between piles at <i>IYL</i> in <i>C3</i> configuration.....	364
Figure 5-294 : Load Distribution between piles at <i>FYL</i> in <i>C3</i> configuration.....	364
Figure 5-295 : Load Distribution between piles at <i>IYL</i> in <i>C4</i> configuration.....	365
Figure 5-296 : Load Distribution between piles at <i>FYL</i> in <i>C4</i> configuration.....	365
Figure 5-297 : Load Distribution between piles at <i>IYL</i> in <i>C5</i> configuration.....	365
Figure 5-298 : Load Distribution between piles at <i>IYL</i> in <i>C5</i> configuration.....	365
Figure 5-299 : Load Distribution between piles at <i>IYL</i> in <i>C6</i> configuration.....	366
Figure 5-300 : Load Distribution between piles at <i>FYL</i> in <i>C6</i> configuration.....	366
Figure 5-301 : Load Distribution between piles at <i>IYL</i> in <i>C7</i> configuration.....	367
Figure 5-302 : Load Distribution between piles at <i>FYL</i> in <i>C7</i> configuration.....	367
Figure 5-303 : Load Distribution between piles at <i>IYL</i> in <i>C8</i> configuration.....	367
Figure 5-304 : Load Distribution between piles at <i>FYL</i> in <i>C8</i> configuration.....	367
Figure 5-305 : Load Distribution between piles at <i>IYL</i> in <i>C9</i> configuration.....	368
Figure 5-306 : Load Distribution between piles at <i>FYL</i> in <i>C9</i> configuration.....	368
Figure 5-307 : Comparison of Stiffness with PDR and Clancy .....	369
Figure 5-308 : Comparison of Load Shared by pile with PDR .....	369
Figure 5-309 Few long piles with relatively large spacing .....	375
Figure 5-310 Few short piles with relatively large spacing .....	375
Figure 5-311 Large number of piles with relatively small spacing .....	375
Figure 5-312 : Pile bending in PRF with short piles ( $L/d=10$ at $I_d=60\%$ ) after test .....	376
Figure 5-313 : Pile bending in PRF with medium piles ( $L/d=20$ at $I_d=60\%$ ) after test .....	377
Figure 5-314 : Load settlement curve of single pile .....	382
Figure 5-315 : Load settlement curve of unpiled raft and pile group .....	382