

TABLE OF CONTENTS

	Page	
	No.	
Acknowledgements	i	
Table of Contents	iv	
List of Tables	xii	
List of Figures	xiii	
Abbreviations and Notations	xxvi	
Abstract	xxvii	
Chapter – 1	Introduction and Research Objectives	
1.1	Background and origin of the topic	1
1.2	Research Motivation	7
1.3	Research Objectives	8
1.4	Structure of the Thesis	9
Chapter – 2	Literature Review	
2.1	Textile Structures	11
2.2	Textile Reinforced Concrete	14
2.3	Composition of cementitious matrix for manufacturing TRC	15
2.4	TRM fabrication methods	18
	2.4.1 Casting	18
	2.4.2 Pre-tensioning (Prestressing)	19
	2.4.3 Hand lay up	21
	2.4.4 Spraying method	21
	2.4.5 Filament Winding	22
	2.4.6 Pultrusion	23
	2.4.7 Combined additive manufacturing of TRC	24
2.5	Hybrid yarn-based structure	25
	2.5.1 Commingled yarn	26
	2.5.1.1 Commingled yarn using compressed	26

	air jets	
	2.5.1.2 Online commingling process	28
	2.5.2 Air-jet textured yarn	29
	2.5.3 Powder coated yarn	29
	2.5.4 Cable yarn	30
	2.5.5 DREF spun core-sheath yarn	31
	2.5.6 Braided structure	33
2.6	2-D woven fabric	34
2.7	2-D woven fabric based FRCM	34
	2.7.1 Fibre type	36
	2.7.2 Reinforcement ratio and number of fabric layers	36
	2.7.3 Embedment length	37
	2.7.4 Yarn twisted configuration	37
	2.7.5 Yarn fineness	37
	2.7.6 Yarn geometry and pick density	38
	2.7.8 Fabric grid opening size	39
	2.7.9 Fabric weave design	40
	2.7.10 Hybrid fabric	41
2.8	Non-crimp fabrics for TRC reinforcement	42
2.9	Methods of improving fibre-concrete bonding	43
	2.9.1 Surface modification of FRP rods	43
	2.9.2 Modified braided rod structure	43
2.10	Coating textiles	45
	2.10.1 Coating of filament bundle	46
	2.10.2 Mineral-impregnated carbon fibre composites	47
	2.10.3 Plasma treatment	49
	2.10.4 Nano coating	49
	2.10.5 Resin coating of woven fabric	50
2.11	Inclusion of short fibres as secondary reinforcement in TRC	52
2.12	Mechanical characteristics of FRCM specimens	55
	2.12.1 Strain-softening and strain-hardening response of FRC composites	55

	2.12.2	Yarn pull-out behaviour in FRCMspecimens	57
	2.12.3	Uniaxial tensile behaviour of FRCM specimens	58
	2.12.4	Flexural behaviour of FRCM specimens	59
	2.13	Gaps in Literature	59
Chapter – 3		Materials and Methods	
	3.1	Raw material selection	61
	3.1.1	Types of filament rovings and fibres used	61
	3.1.2	Epoxy resin and hardener	63
	3.1.3	Components of Mortar mix	63
	3.2	Development of Hybrid yarn structures	64
	3.2.1	Core-sheath yarn development using the DREF 3 spinning system	64
	3.2.2	Cable yarn structure development using the filament wrapping method	66
	3.2.3	Cable yarn structure development using the braiding method	67
	3.2.4	Thermal treatment of twisted polyester yarn and hybrid yarn structures	69
	3.3	Development of plain-woven Scrim fabric structures	75
	3.4	Fabrication of fabric composites	83
	3.4.1	Production of thermoplastic fabric composite using the compression moulding process	83
	3.4.2	Production of thermoset fabric composites via epoxy resin coating	83
	3.5	Cross-section examination of yarn samples	84
	3.5.1	Preparation of yarn samples for cross-section examination	84
	3.5.2	Microscopic examination of yarn cross-sections	84
	3.6	Mortar mix design and fabrication of unreinforced, yarn-reinforced, and fabric-reinforced mortar specimens for mechanical testing	86
	3.6.1	Fabrication of formwork for casting mortar specimens for pull-out, tensile, and flexural test	86

3.6.2	Formulation of mortar mix proportions	86
3.6.3	Mortar mixing, casting and curing of mortar specimens	87
3.6.4	Mortar specimen compaction and curing	89
3.6.5	Slump test for mortar consistency	90
3.6.6	Preparation of YRCM specimens for yarn pull-out testing	91
3.6.7	Preparation of FRCM specimens for yarn pull-out testing	91
3.6.8	Preparation of FRCM specimens for uniaxial tensile testing	91
3.6.9	Preparation of FRCM specimens for flexural testing	91
3.7	Tensile testing method for yarn, fabric, and fabric composite specimens	91
3.8	Compression strength testing method for mortar cube specimens	93
3.9	Split tensile testing method for mortar cylinder specimens	93
3.10	Yarn pull-out testing method for YRCM and FRCM specimens	94
3.11	Uniaxial tensile testing method for FRCM specimens	96
3.12	Flexural testing method for FRCM specimens	98
Chapter – 4	Results and Discussions	
4.1	Cross-section micrograph of yarn specimens	100
4.1.1	Cross-section micrographs of DREF spun core-sheath yarn	100
4.1.2	Cross-section micrographs of parent, epoxy coated and hybrid yarn	101
4.2	Tensile behaviour of yarn and fabric specimens	104
4.2.1	Tensile behaviour of parent ARglass yarn, hybrid yarn and fabricspecimens	107
4.2.2	Tensile behaviour of parent basalt yarn, hybrid	109

	yarn and fabricspecimens	
4.2.3	Effect of mesh opening on tensile behaviour of hybrid yarn based thermoplastic fabric compositespecimens	111
4.2.4	Tensile behaviour of parent carbon yarn, hybrid yarn and fabricspecimens	112
4.2.5	Comparison of tensile behaviour of parent and hybrid ARglass, basalt, carbon yarn and fabricspecimens	115
4.2.6	Discussion on tensile behaviour of parent yarn, hybrid yarn and fabricspecimens	116
4.3	Compression behaviour of Mortar Cubes	117
4.4	Split tensile behaviour of Mortar Cylinders	117
4.5	Yarn pull-out behaviour of yarn reinforced cementitious mortar specimens	118
4.5.1	Yarn pull-out behaviour of AR-glass YRCM specimens	118
4.5.2	Yarn pull-out behaviour of Basalt YRCM specimens	121
4.5.3	Yarn pull-out behaviour of Carbon YRCM specimens	123
4.5.4	Comparison of yarn pull-out behaviour of different YRCM specimens	125
4.6	Yarn pull-out behaviour of FRCM specimens	126
4.6.1	Yarn pull-out behaviour of AR-glass FRCM specimens	127
4.6.2	Yarn pull-out behaviour of Basalt FRCM specimens	128
4.6.3	Yarn pull-out behaviour from Carbon FRCM specimens	131
4.6.4	Influence of yarn embedment length on pull-out behaviour	132
4.6.5	Comparison of yarn pull-out behaviour across	134

	different FRCM specimens	
4.6.6	Discussion on yarn pull-out behaviour of YRCM and FRCM specimens	135
4.7	Uniaxial tensile behaviour of FRCM specimens	137
4.7.1	Uniaxial tensile behaviour of AR-glass FRCM specimens	137
4.7.2	Uniaxial tensile behaviour of Basalt FRCM specimens	140
4.7.3	Comparison of tensile behaviour of parent basalt fabric, hybrid yarn-based basalt TP and TS fabric composite based FRCM specimens	143
4.7.4	Effect of the number of fabric reinforcement layers on the tensile behaviour of FRCM specimens	145
4.7.5	Effect of fabric mesh opening size on the tensile behaviour of FRCM specimens	146
4.7.6	Uniaxial tensile behaviour of Carbon FRCM specimens	147
4.7.7	Comparison of uniaxial tensile behaviour of different FRCM specimens	149
4.7.8	Crack pattern of FRCM specimens subjected to uniaxial tensile test	150
4.8	Flexural behaviour of FRCM specimens	154
4.8.1	Flexural behaviour of ARglass FRCM specimens	154
4.8.2	Flexural behaviour of Basalt FRCM specimens	157
4.8.3	Comparison of flexural behaviour of parent basalt fabric, hybrid yarn-based basalt TP and TS fabric composite based FRCM specimens	160
4.8.4	Effect of fabric mesh opening size on the flexural behaviour of FRCM specimens	162
4.8.5	Effect of the number of fabric reinforcement layers on the flexural behaviour of FRCM specimens	163

	4.8.6	Flexural behaviour of Carbon FRCM specimens	166
	4.8.7	Comparison of flexural behaviour of different FRCM specimens	168
Chapter – 5		Summary and Conclusions	
	5.1	Background	170
	5.2	Cross-section micrograph of yarn specimens	171
	5.3	Tensile behaviour of yarn and fabric	171
	5.4	Cylinder split tensile behaviour	171
	5.5	Yarn pull-out behaviour of YRCM specimens	172
	5.6	Yarn pull-out behaviour of FRCM specimens	172
	5.7	Uniaxial tensile behaviour of FRCM specimens	173
	5.7.1	Comparison of tensile behaviour of parent, epoxy coated and hybrid yarn-based AR-glass, basalt and carbon FRCM specimens	173
	5.7.2	Comparison of tensile behaviour of parent basalt fabric, hybrid yarn-based basalt TP and TS fabric reinforced FRCM specimens	174
	5.7.3	Effect of number of layer reinforcement on tensile behaviour of FRCM specimens	174
	5.7.4	Effect of mesh size opening of fabric on tensile behaviour of FRCM specimens	175
	5.8	Flexural behaviour of FRCM specimens	176
	5.8.1	Comparison of flexural behaviour of parent, epoxy coated and hybrid yarn-based AR-glass, basalt and carbon FRCM specimens	176
	5.8.2	Comparison of flexural behaviour of parent basalt fabric, hybrid yarn-based basalt TP and TS fabric reinforced FRCM specimens	176
	5.8.3	Effect of number of layer reinforcement on flexural behaviour of FRCM specimens	177
	5.8.4	Effect of mesh size opening of fabric on flexural behaviour of FRCM specimens	178

5.9	Scope for Future work	179
	List of References	180
	Curriculum Vitae	198
	List of Publications	199