

LIST OF TABLES

Table No.	Title of Table	Page No.
Table 2.1	Typical fibres used in concrete and their properties	12
Table 2.2	Composition of cementitious matrix used for manufacturing TRC used in various studies	17
Table 3.1	Basic characteristics of the yarns (rovings/tow) used in this study.	62
Table 3.2	Basic properties of the resin and hardener.	63
Table 3.3	Properties of the different binders as mortar constituents.	63
Table 3.4	Process parameters in DREF3 spinning machine.	65
Table 3.5	Process parameters used in thermal treatment operation.	71
Table 3.6	Yarn construction details with codes for different yarn structure used in this study.	74 – 75
Table 3.7	Fabric construction details of various fabrics used in this study.	78 – 82
Table 3.8	Mix proportions of mortar ingredients by weight ratio for FRCM preparation.	87
Table 4.1	Measured perimeter, cross-sectional area and shape factor of yarn specimens using microscope.	103
Table 4.2	Tensile load and displacement values of uncoated, epoxy coated and hybrid yarns of ARG, basalt, and carbon.	105
Table 4.3	Tensile load and displacement values of uncoated, epoxy coated and hybrid yarn-based fabrics of ARG, basalt, and carbon.	106
Table 4.4	Crack details of failed FRCM specimens after uniaxial tensile test. (n – number of specimens)	151