

LIST OF FIGURES

Figure No.	Title	Page
1.1	Common Rail Diesel Fuel injection system	2
1.2	Common Rail Diesel Fuel injector	3
1.3	Fuel injector nozzle types	4
1.4.	Sketch of nozzle entrance that shows the cavitation inception	4
1.5	Evolution of cavitation flow inside fuel injector nozzle	5
1.6	Primary and secondary spray breakup	6
1.7	Governing mechanism for primary spray break-up	7
2.1	Cavitation observed by Nurik ^[9] in the transparent nozzle	12
2.2	Comparison of hole cavitation for the enlarged (left with CN=5.5) and the real size (right with CN=5.4) nozzle, Arcoumanis et al. ^[13]	13
2.3	Two-dimensional throttle geometry and cavitation field using interferometry imaging (a, b) Winklhofer et al. ^[14] and (c, d) Mauger et al. ^[17]	14
2.4	Real size single hole transparent cylindrical nozzle (d=0.51mm, L=1mm) used by Payri et al. ^[15]	15
2.5	Transparent nozzle (d=0.3 mm, L=1 mm) fabricated by Selective Laser Etching (SLE) method to withstand 250 bar of pressure used by Kirsch et al. ^[19]	16
2.6	Compilation of experimental nozzle discharge coefficient. Data are plotted on loglog axes. Schmidt and Corradini ^[5]	18
2.7	Sketch of the atomization processes of liquid fuel injected from a nozzle, Reitz ^[64]	24
2.8	Spray cone angle with different cavitation flow pattern map, Abbasiasl T. et al. ^[94]	28
2.9	Two types of cavitation patterns obtained by shadow photography Cao T et al. ^[97]	29
2.10	String cavitation at selected needle lift during the SOI Gavaises et al ^[103]	30
3.1	Spray breakup mechanism with KHRT instability ^[104]	36
3.2	Conceptual diagram of the Two-step cavitation coupled spray breakup method	40

3.3	Schematic diagram for test set up to visualization of cavitation flow	41
3.4	Actual image of test set up to visualization of cavitation flow	42
3.5	Details of cavitation nozzle-1 (CN1), L= 10 mm, W _n =8mm, t=8mm	42
3.6	Details of cavitation nozzle-2 (CN2), L= 10mm, W _n =5mm, t=2mm	43
3.7	Schematic diagram of cavitation nozzle 3 (CN3)	44
3.8	Development stages of the cavitation nozzle-3 (CN3)	44
3.9	Microscopic image of the cavitation nozzle-3(CN3)	44
3.10	Details of cavitation nozzle-4(CN4)	45
3.11	Details of cavitation nozzle-5(CN5)	45
3.12	Schematic diagram of test set up to visualization of spray characteristics	48
3.13	Actual image of test set up to visualization of spray characteristics	48
3.14	Graphic user interface of DaVinci Resolve	49
3.15	Graphic user interphase of Autodesk Inventor	50
3.16	Image processing steps	51
3.17	Schematic diagram of experimental setup for biodiesel production using hydrodynamic cavitation	51
3.18	Actual image of experimental setup for biodiesel production using hydrodynamic cavitation	52
4.1	Two-dimensional throttle (transparent rectangular cross-section) geometry	53
4.2	Cavitation field capture using interferometry imaging technique ^[14]	54
4.3	Computational domain with its dimension	54
4.4	Grid generation with refinement at throttle inlet	55
4.5	Effect of number of mesh elements on the mass flow rate of fuel	55
4.6	Quantitative comparison of fuel mass flow rate with experimental results	56
4.7	Comparison of the velocity profiles at 53 μm from the nozzle inlet	56
4.8	Qualitative comparison of Liquid volume fraction with experimental results ^[14]	58
4.9	Volume fraction of vapor at with different of turbulence model	58
4.10	Comparision of turbulence model based on the mass flow rate of fuel	59

4.11	Comparison of the SS and the ZGB cavitation model based on the volume fraction of vapor	60
4.12	Comparison of the predicted mass flow rate with the Mixture and VOF multiphase model in the SS & ZGB cavitation model combination at different pressure differentials	60
4.13	Comparison of vapor fraction contour between the mixture and VOF model in conjunction with dispersed and sharp interface option at $\Delta P=85$ bar.	61
4.14	Percentage error mass flow rate of the fuel with different combinations of numerical models	62
4.15	Vapour bubble formation and its development inside the throttle at $\Delta P=85$ bar	63
4.16	Boundary condition with detail mesh geometry	64
4.17	Effect of mesh elements on spray penetration length	64
4.18	Spray developments compared with the experimental work	65
4.19	Comparison of Spray tip penetration of different spray breakup models with experimental data	66
4.20	X-ray CT image at the injector's central cross ^[106,107]	68
4.21	Two-dimensional axis-symmetric wireframe geometry ^[106, 107]	68
4.22	Mesh generation for internal flow	69
4.23	Mesh sensitivity study for internal flow	69
4.24	Geometry and mesh quality for spray simulation	70
4.25	Comparison and validation of Two-step coupled method with experimental and numerical work of Payri et al. ^[109]	73
4.26	Comparison of theoretical and actual mass flow rate of water at different injection pressure.	74
4.27	Macroscopic spray characteristics (a) spray tip penetration (b) spray cone angle (c) spray area ^[111]	84
4.28	Development of spray after start of injection (SOI)	85
4.29	Comparison of STP with empirical model	85
4.30	Orifice plates with different slit cross section	87
4.31	Temperature rise with respect to time for different orifice	87
4.32	Sample collected at every five minutes of time interval	88

4.33	Percentage yield conversion with respect to time	88
4.34	Waste cooking oil to Bio-diesel	89
5.1	Winklhofer nozzle with its boundary conditions	90
5.2	Velocity profile at a location $x=0.053$ mm from the nozzle inlet	91
5.3	Pressure distribution along with the axial distance	91
5.4	Comparison of Discharge coefficient vs. Cavitation parameter with Nurik's theoretical model ^[9]	93
5.5	Effect of k-factor on the mass flow rate of fuel at a variable pressure difference	94
5.6	Comparison of the vapor fraction contour at different k-factor values	94
5.7	Effect of cavitation parameter on discharge coefficient for diesel and bio-diesel	95
5.8	Details of various simulation case for Spray C injector	96
5.9	Pixel method to calculate effective diameter	97
5.10	Quantitative comparison of the simulation result with Tahmasebi et al. ^[110]	98
5.11	Results contour for ECN spray C injector (Case-1)	99
5.12	DPM concentration and velocity of spray	100
5.13	Steps for image processing and spray cone angle	101
5.14	Vapor fraction contour with different pressure and turbulent mode	103
5.15	Outlet velocity at different combination of inlet and back pressure	104
5.16	Mass flow rate at different combination of inlet and back pressure	104
5.17	Effective outlet diameter at different combination of inlet and back pressure	105
5.18	Corrected mass flow rate at different combination of inlet and back pressure	105
5.19	Static pressure distribution along the nozzle length	107
5.20	Liquid volume of fraction profile at nozzle outlet	108
5.21	Velocity profile at different inlet and outlet pressure	110
5.22	Turbulent kinetic energy profile at different inlet and outlet pressure	111
5.23	Spray shape at different inlet and outlet pressure	112

5.24	Cavitation coupled spray breakup	113
5.25	MPD and SMD at different inlet and outlet pressure	114
5.26	Different cavitation stages coupled with spray results with scaled up nozzle (CN 3)	116
5.27	Actual image of cavitation bubbles and sheet cavitation inside the nozzle	116
5.28	Spray cone angle vs. Injection pressure (CN 3W)	117
5.29	Injection pressure vs. Cavitation number (CN 3W)	118
5.30	Reynolds number vs. Cavitation number (CN 3W)	118
5.31	Cavitation number vs Characteristics length (L_c/L)	119
5.32	Reynolds number vs Coefficient of discharge (CN 3W)	120
5.33	Reynolds number vs Spay cone angle (CN 3W)	120
5.34	Different stages of the cavitation for diesel fuel	121
5.35	Pressure vs volume flow rate for water and diesel (CN 3WD)	122
5.36	Reynolds number vs Cavitation number for Water and diesel (CN 3WD)	122
5.37	Geometry, boundary condition and mesh details.	123
5.38	Pressure, velocity and vapor fraction contour for CN 4	124
5.39	Experimental results for CN 4 using water and diesel	124
5.40	Acrylic nozzle with its dimension and mesh details	125
5.41	Different cavitation stages coupled with spray results with scaled up nozzle	126
5.42	Effect of pressure on (a) Volume flow rate (b) Spray cone angle (c) L_{cav}/L (d) C_d	128
5.43	Reynolds number vs Spray cone angle (CN 5WDB)	129
5.44	Reynolds number vs Cavitation number (CN 3WD & CN 5WDB)	130
5.45	Comparison of CFD results with experimental image for diesel fuel	131
5.46	Pressure distribution along the axis	132
5.47	Velocity profile at (a) Inlet of the nozzle (b) Outlet of the nozzle	132
5.48	Image processing steps	133
5.49	Spray development at different injection pressure (a) 100 bar (b) 300 bar (c) 500 bar	135

5.50	Spray development for different fuels (a) Diesel (b) B20 (Tallow) (c) B20 (WCO)	136
5.51	Spray tip penetration of diesel fuels at different injection pressure	137
5.52	Spray tip penetration foe diesel, tallow & WCO (a) 150 bar (b) 300 bar (c) 500 bar	138
5.53	Spray cone angle at different time interval	138
5.54	Calculation of SCA using two-step coupled method	1.9
5.55	Cavitation inception and super cavitation at different L/d ratio	140
5.56	Cavitation umber vs L/d ratio	141

