

## List of Figures

<b>Figure Number</b>	<b>Figure Description</b>	<b>Page No</b>
2.1	Trend of global greenhouse gas generation till 2020 in terms of carbon di-oxide from fossil fuels	6
2.2	Global greenhouse as emissions by economic sector	7
2.3	Different components of tyre	8
2.4	Rolling resistance contributed by different components of tyre	9
2.5	Payne effect and contribution of shear modulus for carbon black	12
2.6	Illustration of applied sinusoidal strain and measured shear stress for a typical viscoelastic material.	14
2.7	Correlation of BPST (wet skid number) of tyre and the $\tan\delta$ value of corresponding tyre tread compound measured at 0°C and 10Hz frequency.	17
2.8	Schematic representation of road texture and abrasive tread wear	18
2.9	Schematic representation of hysteresis wear loss	19
2.10	Magic triangle property of tyre tread compound	21
2.11	A correlation of particle size in term of its reciprocal with surface area of carbon black	23
2.12	Schematic representation of carbon black particle and formation of structure	24

2.13	Schematic representation of void volume and structure of carbon black	25
2.14	(a) TEM analysis of aggregates shows different size of aggregates present in carbon black. (b) A discrete aggregate of carbon black formed by fused of carbon particles as shown in higher magnification of TEM analysis	27
2.15	A typical aggregate size distribution and cumulative distribution of carbon black	28
2.16	Schematic representation of carbon black surface chemistry	29
2.17	a) Surface phenomenon of ASTM grade carbon black and Inversion carbon black, (b) Concept of high molecular intact with inversion carbon bon black surface compared to ASTM grade carbon black.	32
3.1	Chemical structure of natural rubber: Cis-Poly-1, 4-Isoprene	43
3.2	Chemical structural unit of polybutadiene rubber (cis-configuration)	45
3.3	A schematic representation of Styrene butadiene rubber molecular unit formation by reaction of styrene and butadiene monomers.	46
3.4	Modes of functionalization at different ends of functionalized SSBR	47
3.5	Chemical structure of (A) 2,2,4-trimethyl-1,2-dihydroquinoline (TMQ) and (B) N-(1,3-Dimethylbutyl)-N'-phenyl-p-phenylenediamine (6PPD)	50
3.6	Chemical configuration of rhombic Sulphur (S8)	52
3.7	Absorptometer Equipment (Brabender® Absorptometer “C”)	55

3.8	Schematic representation dispersion injection distance (S) and detection distance (Rd)	56
3.9	Schematic representation furnace reactor for carbon black manufacturing	59
3.10	Typical rheological graph of rubber compound	63
4.1	Comparison of aggregate size distribution of carbon black (A) Aggregate size distribution of Sx-1, Sx-2, Sx-3 (B) Aggregate size distribution of Sx-4 and SX-5.	77
4.2	Transmission electron microscopy: (A) Sx-1 carbon black (B) Sx-2 carbon black, (C) Sx-3 carbon black (D) Sx-4 carbon black (E) Sx-5 carbon black.	78
4.3	Schematic representative of inter-particle distance with two similar particle size vis-à-vis dissimilar particle size	82
4.4	Shear modulus of compound with strain sweep, (A) Compound Sx-1RC, Sx-2RC, Sx-3RC and (B) Compound Sx-4RC, Sx-5RC.	83
4.5	Hysteresis loss (loss tangent value) of rubber compounds, measured at 60°C.	85
4.6	Abrasion loss (volume loss in mm <sup>3</sup> ) of rubber compound	87
4.7	Typical example of aggregate size distribution of carbon black with different dV/dD values across the aggregate size.	89
4.8	Aggregate size distribution of different carbon black having different extent of large size aggregate with dissimilar characterization of dV/dD at the large aggregate size region.	90
4.9	Aggregate size distribution of carbon black with dissimilar dV/dD value at higher aggregate size region.	91
4.10	Reciprocal of (dV/dD) value at 150 nm aggregate diameter	92

4.11	Transmission Electron Microscopy of Sy-1 Carbon black - (a) aggregate constructed with lower particle size (b) aggregate constructed with similar particle size.	94
4.12	Transmission Electron Microscopy of Sy-2 Carbon black - (a) aggregate constructed with lower particle size (b) aggregate constructed with bigger particle size.	94
4.13	Transmission Electron Microscopy of Sy-3 Carbon black - (a) aggregate constructed with lower particle size (b) aggregate constructed with bigger particle size.	95
4.14	Transmission Electron Microscopy of Sy-4 Carbon black - (a) aggregate constructed with lower particle size (b) aggregate constructed with bigger particle size.	95
4.15	Payne effect of rubber compound	98
4.14	Loss tangent value of rubber compound at 60°C.	100
4.15	Heat buildup properties of rubber compounds	100
5.1	Aggregate size distribution of different carbon black grades (HP01, HP02, HP03, HP04, HP05, HP06, HP07)	109
5.2 (A&B)	HRTEM images and characteristics of particle size of carbon black grade(A) HP01 grade (B) HP02 grade.	110
5.2 (C&D)	HRTEM images and characteristics of particle size of carbon black grade (C) HP03 grade (D) HP04 grade.	110
5.2 (E&F)	HRTEM images and characteristics of particle size of carbon black grade (E) HP05 grade (F) HP06 grade.	111
5.2 G	HRTEM images and characteristics of particle size of carbon black (G) HP01 grade	111
5.3	The trend of shear modulus with shear strain sweep of different rubber compounds.	116

5.4	Payne effect of the rubber compounds with $d_{10}$ value of corresponding carbon black	117
5.5	Trend of heat buildup property (rise in sample temperature) with Payne effect	119
5.6	Trend of heat buildup property with $d_{10}$ value of carbon black aggregate size distribution	120
5.7	Trend of $\tan\delta$ values with ‘aggregate size distribution co-efficient’ parameter (A) where $n=1$ , $a=2$ , $b=1$ .	121
5.8	Trend of abrasion resistance index of rubber compound with ‘structure co-efficient parameter ( $\hat{S}$ ) of carbon black	124
5.9	Abrasion resistance Index of rubber compounds	125
6.1	Schematic representative of carbon black surface morphology and functionality	130
6.2	High-resolution transition electron microscopy (HRTEM) of carbon black (A) non-oxidized carbon black (B) oxidized carbon black with ozone treatment	132
6.3	HRTEM images of carbon black aggregates/agglomerates suspended in water-dispersion (A) non-oxidized carbon black, where aggregates form agglomeration (A) Oxidized carbon black by Ozone treatment for 30 minutes where aggregates remain discrete particles and scatter in the system.	134
6.4	XRD Pattern of control carbon black and ozone treated carbon black.	135
6.5	Thermogravimetric analysis of carbon black in presence of oxygen atmosphere	136

6.6	Increased in volatile content due to functionalization of carbon black.	139
6.7	pH of carbon black- changes due to presence of functionalized	140
6.8	XRD pattern of carbon black characterized with different oxidation time	142
6.9	Thermogravimetric analysis, in presence of oxygen atmosphere, of carbon black characterized with different ozone treatment time.	143
6.10	TEM of rubber compounds (A) Controlled SBR-BR compound, (B) Experimented SBR-BR compound (SBO-30) where 30 min ozone treated carbon black used, (C) Control SSBR-BR compound, (D) Experimented SSBR-BR compound (SSBO-30) where 30 min ozone treated carbon black used.	147
6.11	Trend of Payen effect of rubber compound with ozone treatment time of corresponding carbon black.	149
6.12	Trend of modulus of rubber compound with ozone treatment time of corresponding carbon black	151
6.13	Trend of tensile strength of rubber compound with ozone treatment time of corresponding carbon black.	152
6.14	Abrasion resistance index of rubber compounds	152
6.15	Trend of loss tangent value of rubber compounds with temperature scan (A) SSBR-BR rubber compound (B) SBR1712-BR rubber compounds	154
6.16	Trend of storage modulus of rubber compounds with temperature scan (A) of SBR1712-BR rubber compounds (B) SSBR-BR rubber compounds	156

6.17	Magic triangle properties of different SBR1712-BR rubber compounds	157
6.18	Magic triangle properties of different SSBR-BR rubber compounds	158
7.1	Schematic representative of reaction mechanism between benzyl tri ethyl ammonium chloride and carbon black	165
7.2	Aggregate size distribution of carbon black on BTEAC treatment and comparison with control carbon black	166
7.3	Thermogravimetric analysis of BTEAC treated carbon black vis-à-vis non-treated carbon black	168
7.4	Transmission electron microscopic analysis on aggregate and structural views of BTEAC treatment of carbon black (A) N330 Control carbon black (B) BTEAC treated N330 carbon black.	169
7.5	Transmission electron microscopy to visualize particle size of carbon black (A) N330 Control carbon black (B) BTEAC treated N330 carbon black	169
7.6	AFM images of compounds (a) AFM image of control compound based on SSBR-BR system (SS0), (b) AFM image of 1.0 % BTEAC modified carbon black based compound based on SSBR-BR (SS 1.0), (c) AFM image of control compound based on emulsion SBR-BR system (b) AFM image of 1.0 % BTEAC modified carbon black based on emulsion SBR-BR system (SB1)	174
7.7	Bound Rubber Content of Compounds with concentration of BTEAC in carbon black	176
7.8	Trend of shear modulus of compound with strain amplitude (A) SBR-BR compounds (B) SBR1712-BR compounds	177

7.9	Trend of storage modulus with strain sweep at 60°C (A) SSBR-BR compounds, (B) SBR-BR compounds	180
7.10	Trend of loss tangent value with strain sweep at 60°C (A) SSBR-BR compounds (B) SBR1712-BR compounds	181
7.11	Mechanical properties of rubber compounds (A) Tensile strength (B) Elongation at break (C) Modulus at 300% elongation (D) Abrasion resistance Index	182
7.12	Trend of shear modulus of rubber compound with shear strain amplitude	185
7.13	Trend of Payne effect with loading of carbon black and compare with Payne effect of control compounds.	187
7.14	Trend of $\tan\delta$ values of rubber compounds measured at 60°C and 0°C.	189
7.15	Magic triangle properties of rubber compounds (A) SB0-55 compound vis-à-vis SB1-45 Compound (B) SB0-55 compound vis-à-vis SB1-50 Compound (C) SB0-55 compound vis-à-vis SB1-55 Compound (D) SB0-55 compound vis-à-vis SB1-60 Compound (E) SB0-55 compound vis-à-vis SB1-65 Compound	191