

## LIST OF TABLES

| Sr. No.   | Title   | Page No. |
|-----------|---|----------|
| Table 1.1 | Physical and Chemical Properties of pure liquid   | 12       |
| Table 2.1 | Features of polar and non-polar binary liquids  | 26       |
| Table 2.2 | Ideal circuit elements used in different models   | 62       |
| Table 3.1 | The sources and grades, CAS No, IUPAC Name and purity of chemicals used in the present work   | 72       |
| Table 3.2 | Specifications of DAK-3.5 probe   | 78       |
| Table 4.1 | Comparison of static permittivity ( $\epsilon_0$ ) of pure compounds (n-Hexanol and DMF) with literature data at different temperatures   | 109      |
| Table 4.2 | Values of dielectric constant ( $\epsilon'$ ), dielectric loss ( $\epsilon''$ ), and AC conductivity ( $\sigma$ ) of n-Hexanol and DMF at different frequencies at 303.15 K temperature.  | 115      |
| Table 4.3 | Values of fitted parameters $\epsilon_0$ (Static permittivity), $\Delta\epsilon_{EP}$ (Relaxation strength), $\tau_{EP}$ (relaxation time), $\alpha$ (Shape parameter), $\tau'_{EP}$ (Electrode polarization relaxation time) ionic polarization relaxation time ( $\tau_\sigma$ ) and dc conductivity ( $\sigma_{dc}$ ) for various concentration of DMF at different temperatures | 117      |
| Table 4.4 | Comparison of activation energy ( $E_a$ ) of dc conductivity ( $E_{dc}$ ) and ionic conductivity relaxation time ( $E_{\tau_\sigma}$ ) for the binary mixture of DMF and n-Hexanol  | 135      |
| Table 4.5 | Fitted parameters of four element equivalent RC circuit for all concentration (0.0→1.0) double layer relaxation time constant ( $\tau_{EDL}$ ) and geometric relaxation time ( $\tau_g$ ) at 303.15 K   | 142      |
| Table 4.6 | Values of optical dielectric constant ( $\epsilon_{\infty 0}$ ), CNLS fitting parameters high frequency limiting dielectric constant ( $\epsilon_{\infty 1}$ ), dielectric relaxation strength ( $\Delta\epsilon$ ), relaxation time ( $\tau_0$ ) and shape parameter ( $\alpha, \beta$ ) of binary mixtures of n-Hexanol + DMF at different temperatures                           | 149      |
| Table 4.7 | Value of coefficients of R. K. Polynomial, correlation coefficient (R) and standard deviation ( $\delta$ ) for excess dielectric constant ( $\epsilon_0^E$ ), excess inverse relaxation time ( $1/\tau_0^E$ ) and excess high frequency limiting dielectric constant ( $\epsilon_\infty^E$ ) at different temperatures  | 154      |
| Table 4.8 | Determined values of effective kirkwood correlation factor ( $g^{eff}$ ) and corrective kirkwood correlation factor ( $g^f$ ) of mixtures of n-Hexanol and DMF at various temperatures  | 156      |

|           |   |     |
|-----------|---|-----|
| Table 4.9 | The table shows the values of the thermodynamic parameters for mixtures of n-Hexanol and N, N-Dimethylformamide (DMF)   | 159 |
| Table 5.1 | Comparison of static permittivity ( $\epsilon_0$ ) of pure compounds (n-Octanol and DMF) with literature data at different temperatures   | 175 |
| Table 5.2 | Fitted values of the parameters $\epsilon_0$ , $\Delta\epsilon_{EP}$ , $\tau$ and $\alpha$ of the Cole - Cole model for binary mixtures of Octanol and DMF at different temperatures  | 182 |
| Table 5.3 | Variation of relaxation time ( $\tau_{EP}$ ), ionic polarization relaxation time ( $\tau_a$ ) and DC electrical conductivity ( $\sigma_{dc}$ ) for different Volume fraction of DMF in n-Octanol+DMF system at different temperatures   | 196 |
| Table 5.4 | Fitted parameters of three element equivalent RC circuit and geometric time constant ( $\tau_g$ ) for all concentration at different temperatures   | 213 |
| Table 5.5 | Calculated values of Debye length ( $\lambda_D$ ), Ion mobility ( $\mu$ ), Mobile ion concentration ( $P_0$ ), and ion diffusivity (D) for the binary mixtures of n-Octanol and N, N-Dimethylformamide at different temperatures  | 214 |
| Table 5.6 | The CNLS fitting parameters such as $\epsilon_\infty$ , $\Delta\epsilon$ , $\tau$ , and $\alpha$ are determined for different mole fractions of n-Octanol in n-Octanol + DMF mixtures at different temperatures   | 219 |
| Table 5.7 | Value of coefficients of R. K. Polynomial, correlation coefficient (R) and standard deviation ( $\delta$ ) for excess dielectric constant ( $\epsilon_0$ ) <sup>E</sup> and excess inverse relaxation time ( $1/\tau_0$ ) <sup>E</sup> at different temperatures  | 224 |
| Table 5.8 | Determined values of effective Kirkwood correlation factor ( $g^{eff}$ ) and Corrective Kirkwood correlation factor ( $g^f$ ) of mixture of n-Octanol and DMF at different temperatures   | 226 |
| Table 6.1 | Comparison of experimental and literature values of ultrasonic velocity (Uv) and viscosity ( $\eta$ ) for pure liquids (n-Hexanol and N, N-Dimethylformamide (DMF)) at different temperatures   | 238 |
| Table 6.2 | The values of ultrasonic velocity (Uv), adiabatic compressibility ( $\beta$ ), intermolecular free length ( $L_f$ ), acoustic impedance (Z), Rao constant (R) and molar compressibility (B) for binary mixtures of DMF + n-Hexanol at different temperatures  | 242 |
| Table 6.3 | The values of viscosity ( $\eta$ ), relaxation time ( $\tau$ ) free volume (Vf) surface tension ( $\sigma$ ) and thermal conductivity (K) for binary mixtures of DMF + n-Hexanol at different temperatures  | 245 |
| Table 6.4 | Value of coefficients of R. K. Polynomial, correlation coefficient (R) for excess ultrasonic velocity (u) <sup>E</sup> , excess adiabatic compressibility ( $\beta$ ) <sup>E</sup> , excess intermolecular free length ( $L_f$ ) <sup>E</sup> , excess acoustic impedance (Z) <sup>E</sup> , excess viscosity ( $\eta$ ) <sup>E</sup> , excess relaxation time ( $\tau$ ) <sup>E</sup> and excess | 252 |

|           |   |     |
|-----------|---|-----|
|           | Gibb's free energy of activation ( $G^*$ ) <sup>E</sup> at different temperatures   |     |
| Table 6.5 | FT-IR spectra functional group analysis of pure n-Hexanol and DMF and their binary mixtures (0.0→1.0) at room temperature   | 254 |
| Table 7.1 | Comparison of experimental and literature values of ultrasonic velocity ( $U_v$ ), density ( $\rho$ ) and viscosity ( $\eta$ ) for pure liquids (n-Octanol and N, N-Dimethylformamide (DMF)) at different temperatures  | 267 |
| Table 7.2 | The values of ultrasonic velocity ( $U_v$ ), adiabatic compressibility ( $\beta$ ), intermolecular free length ( $L_i$ ), acoustic impedance ( $Z$ ), Rao constant ( $R$ ) and molar compressibility ( $B$ ) for binary mixtures of DMF + n-Octanol at different temperatures   | 272 |
| Table 7.3 | Evaluated parameters of surface tension ( $\sigma$ ) and relaxation time ( $\tau$ ) for mole fraction of DMF (0.0→1.0) at various temperatures  | 274 |
| Table 7.4 | Values of coefficients ( $a_0, a_1, a_2, a_3$ ) of R. K. polynomials with correlation coefficient ( $R$ ) at different temperatures   | 278 |
| Table 7.5 | Determined values of Gibbs energy ( $\Delta G$ ), entropy ( $\Delta S$ ) and enthalpy ( $\Delta H$ ) of activation of viscous flow for different mole fraction of DMF in n-Octanol  | 281 |
| Table 8.1 | Comparison of experimental and literature values of refractive index and density ( $\rho$ ) for pure liquids (n-Hexanol and N, N-Dimethylformamide (DMF)) at different temperatures   | 292 |
| Table 8.2 | Values of refractive index ( $n$ ), density ( $\rho$ ), molar volume ( $V_m$ ), molar refraction ( $R_m$ ), atomic polarization ( $P_A$ ), polarizability ( $\alpha$ ), molecular radii ( $r$ ) and internal pressure ( $P_{int}$ ) for the binary liquid mixtures of n-Hexanol with N, N-Dimethylformamide at different temperatures | 295 |
| Table 8.3 | Value of coefficients of R. K. Polynomial, correlation coefficient ( $R$ ) for excess refractive index ( $n$ ) <sup>E</sup> , excess molar volume ( $V_m$ ) <sup>E</sup> , excess reduce volume ( $V_m/R_m$ ) <sup>E</sup> and excess internal pressure ( $P_{int}$ ) <sup>E</sup> at different temperatures                          | 301 |