

# List of Figures

---

Figure 1.1	Mechanical/structural members of different cross-sectional shapes subjected to fluid flow .....	2
Figure 2.1	Flow around circular cylinder.....	6
Figure 2.2	Flow around circular Cylinder for (a) $Re \cong 0$ and (b) $Re = 26$ [13].....	7
Figure 2.3	Flow around single circular cylinder at various Reynold numbers [24].....	8
Figure 2.4	Lift force and drag force coefficients variation with respect to Reynolds number for flow on a circular cylinder, dashed regions represent the scatter of experimental data [7].....	9
Figure 2.5	Schematic of inviscid shear flow around a moving cylinder [39].....	11
Figure 2.6	Streamlines of the shear potential flow around a stationary circular cylinder [39]...	12
Figure 2.7	Arrangements of group of cylinders in fluid flow.....	12
Figure 2.8	Interference regions around the cylinder [59].....	13
Figure 2.9	Interference flow regimes for side-by-side, tandem and staggered arrangements of two pipes [7,62].....	15
Figure 2.10	Flow patterns around cylinders array (a) Triangular ( $30^\circ$ ) (b) Rotated Triangular ( $60^\circ$ ) [65].....	17
Figure 2.11	(Left) Geometry, (Right) Force co-efficients acting on cylinders for different ratio of radii [81].....	18
Figure 2.12	Bilinear transformation from annulus region to the region outside two circles [86].	19
Figure 2.13	(left) Two different diameter circular cylinders in tandem arrangement, (right) The enlarged view of streamlines on surface of cylinders for different $L/D$ [88].....	20
Figure 2.14	Trapezoidal cylinders of different base length ratio and orientations [111].....	22
Figure 2.15	Pressure coefficients on the surface of trapezoidal cylinder [111].....	23
Figure 2.16	Pressure distribution on the periphery of polygonal cylinder [115].....	24
Figure 2.17	Regular polygonal and isotoxal-star polygonal cylinder (left), force co-efficients on polygonal cylinder for $N = 4$ (Right) [121].....	25

Figure 2.18	Conformal transformations from a rectangular shape to a unit circle using combination of Karmann–Trefftz and Theodorsen–Garrick transformation [124]...	26
Figure 2.19	Low-pressure region radius of apices on polygon surfaces [128].....	27
Figure 2.20	Pressure contours around polygon cylinder ( $N = 9$ ) in uniform potential flow, where cylinder orientation $\gamma$ varies from 0 to $\gamma/N$ (a) $\gamma = 0^\circ$ , (b) $\gamma = 5^\circ$ , (c) $\gamma = 10^\circ$ , (d) $\gamma = 20^\circ$ and, (e) variation of first critical Reynolds number with respect to $N$ in viscous flow [129].....	27
Figure 2.21	Pressure co-efficient $C_p$ on the surface of (a) triangular, (b) diamond and (c) square shaped cylinder and, (d) $V_{max}$ at mid shoulder and (e) $V_{max}$ and $C_p$ vs. $N$ [130].....	28
Figure 2.22	Different cross-sectional shapes of piers [148].....	32
Figure 2.23	Arrangement of four cylinders of different shapes: (a) left triangles, (b) right triangles, (c) up/down triangles, (d) down/up triangles (e) squares rotated 45 degree, (f) unrotated squares, (g) regular hexagons, and (h) circles [149].....	32
Figure 2.24	(Left) Triangular wedge placed upstream of circular cylinder in fluid flow, (Right) The pressure co-efficient distribution on the surface of circular cylinder for different spacing ratio $L/D$ [152].....	34
Figure 2.25	Side-by-side configuration of two square cylinders (a) pictorial view (b) two-dimensional view (c) pressure measurement points on the surface of cylinder [155].....	35
Figure 2.26	(a) A body $B_1$ and $B_2$ are forced to oscillate about a hinge at origin of co-ordinate and the body $B_3$ is free to drift, (b) response of body $B_3$ drifting away (left) and towards (right) the two oscillating bodies [165].....	37
Figure 2.27	(a) Downstream cylinder following the forced motion of upstream cylinder, (b) streamlines around two flapping plates in inviscid fluid [166].....	38
Figure 2.28	Conformal maps from annulus to the wing above the ground. The interior circle $C_1$ of annulus is mapped to a wing and outer circle $C_0$ is mapped to ground [163].....	39
Figure 3.1	Mapping from interior of circular cylinder to exterior of polygonal.....	43

Figure 3.2	Composite mapping from interior of circular cylinder to exterior of polygonal shaped cylinder. First, interior of circle is mapped to the exterior of circle by using inverse map, further exterior of circle is mapped to polygonal shaped geometry using hypotrochoid mapping.....	45
Figure 3.3	Various polygonal shapes obtained using hypotrochoidal mapping Function. Continues lines shows hypocycloid with cusps drawn when ( $h = Rr$ ), and dotted lines shows hypotrochoid drawn with finite corner radius when ( $0 < h < Rr$ ).....	46
Figure 3.4	Doubly connected geometries (a) Annulus formed by circle of radius 1 and $q$ in $\zeta$ -plane (b) Two circular cylinder in $\xi$ -plane obtained from annulus through bilinear mapping.....	49
Figure 3.5	Geometries in doubly connected case (a) Annulus formed between the circles of unit radius and radius $q$ in $\zeta$ -plane (b) pair of unit-radius circles in $\xi$ -plane mapped from the annulus in $\zeta$ -plane using bilinear mapping (c) pair of rounded corners polygonal ( $N = 3$ ) and unit radius circular geometry in $Z$ -plane mapped from pair of circles in $\xi$ -plane using hypotrochoidal mapping.....	53
Figure 3.6	Conformal mapping from annulus formed between two concentric circles of unit radius and radius $q$ in $\zeta$ -plane to the pair of two unit-radius circles at distance $H$ in $\xi$ -plane using bilinear mapping and further mapping to the cylinder pair of polygonal sections of different number of sides ( $N_j$ ), corner radius ( $\rho_j$ ), and orientation angle ( $\gamma_j$ ) in $Z$ -plane using hypotrochoidal mapping.....	57
Figure 4.1	Methodology to obtain the flow parameters around single polygonal cylinders in potential flow.....	63
Figure 4.2	Methodology to obtain the flow parameters around two interacting polygonal cylinders.....	64
Figure 4.3	Computational domain, meshing, and boundary conditions for flow around single cylinder.....	65
Figure 4.4	Streamlines of Potential flow (a) around circular cylinder obtained using complex potential function along with hypotrochoidal mapping function for $R_d = 1, h = 0, \forall N \geq 2$ (b) around circular cylinder obtained using inviscid flow model in ANSYS (c) around square shaped cylinder obtained using complex potential	

	function along with hypotrochoidal mapping function for $R_d = 1, h = 0.1, N = 4$	
	(d) around square shaped cylinder obtained using inviscid flow model in ANSYS, hypotrochoidal geometry in ANSYS is generated using key points from MATLAB program.....	67
Figure 4.5	Flow parameters around circular cylinder for $R_d = 1, h = 0, \forall N \geq 2$ , using hypotrochoidal mapping function (a) velocity contour obtained using complex potential function (b) velocity profile obtained using complex potential function (c) velocity contour obtained using ANSYS (d) pressure co-efficient contour obtained using complex potential function (e) pressure co-efficient profile obtained using complex potential function (f) pressure co-efficient contour obtained using ANSYS.	68
Figure 4.6	Potential flow contours obtained using complex potential function along with hypotrochoidal mapping for $R_d = 1, h = 0.1$ , (a) velocity contour for $N = 2$ (b) velocity contour for $N = 3$ (c) velocity contour for $N = 4$ (d) pressure co-efficient contour for $N = 2$ (e) pressure co-efficient contour for $N = 3$ (f) pressure co-efficient contours for $N = 4$ .....	69
Figure 4.7	Potential flow contours obtained using inviscid flow model in ANSYS (a) velocity contour for $N = 2$ (b) velocity contour for $N = 3$ (c) velocity contour for $N = 4$ (d) pressure co-efficient contour for $N = 2$ (e) pressure co-efficient contour for $N = 3$ (f) pressure co-efficient contours for $N = 4$ . Hypotrochoidal geometry in ANSYS is generated using key points from MATLAB program.....	70
Figure 4.8	Flow parameters obtained using complex potential function along with hypotrochoidal mapping for $N = 2, R_d = 1$ , and corner radius $\rho = 1$ to $\rho = 0.26$ , (a) velocity distribution on the surface of elliptic cylinder with major axis parallel to the flow (b) pressure co-efficient distribution on the surface of elliptic cylinder with major axis parallel to the flow (c) velocity distribution on the surface of elliptic cylinder with major axis normal to the flow, (d) pressure co-efficient on the surface of elliptic cylinder with major axis normal to the flow.....	72
Figure 4.9	Flow parameters obtained using complex potential function along with hypotrochoidal mapping for $N = 3, R_d = 1$ , and corner radius $\rho = 1$ to $\rho = 0.16$ , (a) velocity distribution on the surface of triangular cylinder with vertex facing the flow (b) pressure co-efficient distribution on the surface of triangular cylinder with	

	vertex facing the flow (c) velocity distribution on the surface of triangular cylinder rotated by $90^0$ , (d) pressure co-efficient distribution on the surface of triangular cylinder rotated by $90^0$ .....	73
Figure 4.10	Flow parameters obtained using complex potential function along with hypotrochoidal mapping for $N = 4, R_d = 1$ , and corner radius $\rho = 1$ to $\rho = 0.11$ , (a) velocity distribution on the surface of square cylinder with side facing the flow (b) pressure co-efficient distribution on the surface of square cylinder with side facing the flow (c) velocity distribution on the surface of square cylinder rotated by $45^0$ with vertex facing the flow, (d) pressure co-efficient distribution on the surface of square cylinder rotated by $45^0$ with vertex facing the flow.....	74
Figure 4.11	variation of maximum surface velocity $V_{max}/U$ and minimum pressure co-efficient $Cp_{min}$ with normalised corner radius $\rho = 0$ to $\rho = 1$ for different number of sides of polygon.....	75
Figure 4.12	Effect of number of sides of polygonal cylinder on flow parameters, pressure coefficient $Cp$ is shown by dotted line for unit circular cylinder and for inscribed regular polygonal cylinder $Cp$ is shown by continues line.....	76
Figure 4.13	Distribution of pressure co-efficient $Cp$ on the surface of circular cylinder is shown by dotted line and on the surface of polygonal cylinder with number of sides $N = 70$ is shown by continues line.....	76
Figure 4.14	Non-uniform Potential flow (a) streamlines around square shaped cylinder for $R_d = 1, h = 0.1$ due to presence of point vortex, for $\beta = +0.25i$ (b) streamlines around square shaped cylinder due to presence of doublet, for $\beta = +0.25i$ (c) Velocity distribution on surface of circular cylinder ( $R_d = 1, h = 0, \forall N \geq 2$ ) (d) velocity distribution on the surface of square shaped cylinder ( $R_d = 1, N = 4, h = 0.1$ ), for varying doublet location $\beta$ on positive imaginary axis.....	79
Figure 4.15	Non-uniform Potential flow, velocity distribution on surface of (left) circular cylinder ( $R_d = 1, h = 0, \forall N \geq 2$ ) (middle) elliptical cylinder with flow along major axis ( $R_d = 1, N = 2, h = 0.1, \gamma = 0^0$ ), (right) elliptical cylinder with flow normal to major axis ( $R_d = 1, N = 2, h = 0.1, \gamma = 90^0$ ), for varying doublet location $\beta$ on positive imaginary axis.....	80

Figure 4.16	Non-uniform Potential flow, velocity distribution on surface of (left) triangular cylinder ( $R_d = 1, N = 3, h = 0.1, \gamma = 90^\circ$ ), (right) triangular cylinder ( $R_d = 1, N = 3, h = 0.1, \gamma = 180^\circ$ ), for varying doublet location $\beta$ on positive imaginary axis.....	80
Figure 4.17	Non-uniform Potential flow, velocity distribution on surface of (left) triangular cylinder ( $R_d = 1, N = 4, h = 0.1, \gamma = 90^\circ$ ), (right) triangular cylinder ( $R_d = 1, N = 4, h = 0.1, \gamma = 0^\circ$ ), for varying doublet location $\beta$ on positive imaginary axis.....	81
Figure 4.18	Computational domain for the flow around pair of circular cylinders in uniform potential flow.....	82
Figure 4.19	Convergence of $P$ -function (Laurent Series representation), evaluated for $q = 0.4$ , and $\theta = 356^\circ$ to $360^\circ$ inside an annulus region.....	83
Figure 4.20	Convergence of velocity ( $V/U$ ) and pressure co-efficient ( $Cp$ ) on the surface of triangle cylinder ( $N_1 = 3, \rho_1 = 0.1, \gamma_1 = \pi$ ) interacting with downstream diamond shaped cylinder ( $N_2 = 4, \rho_2 = 0.1, \gamma_2 = \pi$ ). The velocity and pressure coefficients are evaluated for input parameters $\theta = 45^\circ$ and for center-to-center distances $H = 2.5, 3$ and $3.5$ .....	83
Figure 4.21	Velocity contours around two circular cylinders of diameter ratio $D/d = 1$ with center distance $H = 1.5d$ in uniform potential flow along the line connecting the centers of cylinders using (a) present method and (b) ANSYS.....	85
Figure 4.22	Velocity contours around two circular cylinders of diameter ratio $D/d = 1$ with center distance $H = 10d$ in uniform potential flow along the line connecting the centers of cylinders using (a) present method and (b) ANSYS.....	85
Figure 4.23	Velocity contours around two circular cylinders of diameter ratio $D/d = 1$ with center distance $H = 1.5d$ in uniform potential flow normal to the line connecting the centers of cylinders using (a) present method and (b) ANSYS.....	86
Figure 4.24	Velocity contours around two circular cylinders of diameter ratio $D/d = 1$ with center distance $H = 10d$ in uniform potential flow normal to the line connecting the centers of cylinders using (a) present method and (b) ANSYS.....	86

Figure 4.25	The dimensionless pressure $P^*$ on the surface of two equal circular cylinders evaluated for the flow direction normal to the line connecting the centres of cylinders and for different center distances $H/d = 1.25, 1.5, 1.75, 2.0, 3.0$ and $\infty$ .	87
Figure 4.26	Velocity (left) and pressure (right) profile on the surface of circular Cylinder 1 ( $d = 2$ ) interacting with circular Cylinder 2 ( $D$ ) for different center-to-center distances ( $Hd$ ) in tandem configuration.....	89
Figure 4.27	Velocity (left) and pressure (right) profile on the surface of circular Cylinder 1 ( $d = 2$ ) interacting with circular Cylinder 2 ( $D$ ) for different center-to-center distances ( $H/d$ ) in side-by-side configuration.....	89
Figure 4.28	Maximum velocity on the surface of circular cylinder at different diameter ratio, for uniform potential flow along the center line and normal to the center line.....	90
Figure 4.29	Minimum pressure co-efficient on the surface of circular cylinder at different diameter ratio, for uniform potential flow along the center line and normal to the center line.....	91
Figure 4.30	Velocity contours around two circular cylinders of diameter ratio $D/d = 2$ with center distance $H = 2.5d$ in uniform potential flow using present method (a) Tandem (c) side-by-side and using ANSYS (b) Tandem (d) Side-by-side.....	92
Figure 4.31	Pressure co-efficient contours around two circular cylinders of diameter ratio $D/d = 2$ with center distance $H = 2.5d$ in uniform potential flow using present method (a) Tandem (c) side-by-side and using ANSYS (b) Tandem (d) Side-by-side.....	93
Figure 4.32	The dimensionless pressure $P^*$ on the surface of two circular cylinders of diameter ratio $D/d = 1, 2, 3$ and $4$ evaluated for the flow direction along the line connecting the centres of cylinders and for center distances $H/d = 3.0$ .....	94
Figure 4.33	Velocity (left) and pressure (right) profile on the surface of circular Cylinder 1 ( $d = 2$ ) interacting with circular Cylinder 2 ( $D$ ) for different diameter ratio.....	95
Figure 4.34	Velocity (left) and pressure (right) profile on the surface of circular Cylinder 1 ( $d = 2$ ) interacting with circular Cylinder 2 ( $D$ ) for different diameter ratio.....	95

Figure 4.35	Velocity and pressure distribution on the surface of circular Cylinder-2 of variable diameter ( $1 \leq D/d \leq 5$ ) interacting with Cylinder-1 of fixed diameter $d = 2$ at distance $H - D + d2 = 1$ in tandem and side-by-side arrangement in uniform potential.....	96
Figure 4.36	Velocity and pressure profile on the surface of circular Cylinder-1 ( $d = 2$ ) interacting with another Cylinder-2 ( $D/d = 1$ ) at distance $H - D + d2 = 1$ in uniform potential flow for different flow angles.....	98
Figure 4.37	Extremum values of velocity (left) and pressure co-efficient (right) around pair of circular cylinders in uniform potential flow for flow angle $0^0 \leq \alpha \leq 180^0$ and distance between the cylinder $H - D + d2 = 1$ .....	99
Figure 4.38	Force co-efficient $C_{fx}$ and $C_{fy}$ acting on the circular cylinders of equal diameters in tandem and side-by-side arrangement for center distance $H/D$ . The flow direction is considered along the line joining the centers of the cylinders in tandem arrangement and normal to the center line in side by side arrangement.....	100
Figure 4.39	Comparison of results of force co-efficients acting on Cylinder-1 in side by side configuration of two equal circular cylinders with the results available from literature and those obtained using ANSYS for flow direction normal to the line connecting the centers of cylinders.....	100
Figure 4.40	Hydrodynamic force co-efficient on the circular cylinder at different diameter ratio, for uniform potential flow along the center line and normal to the center line.....	101
Figure 4.41	Hydrodynamic force acting on cylinder along the center line for angle of attack $0^0 \leq \alpha \leq 180^0$ at diameter ratio $D/d = 1, 2$ and $3$ .....	102
Figure 4.42	Computational domain for the flow around polygonal-circular cylinder pairs in uniform potential flow.....	103
Figure 4.43	Velocity contours around two-cylinders in tandem arrangement with center distance $H = 1.5D$ in uniform potential flow along positive $x$ -direction using complex potential function for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular -circular cylinder pair ( $N = 3, \gamma = 180^0$ and $h = 0.1$ ) (c) square-	

	circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square-circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	106
Figure 4.44	Velocity contours around two-cylinders in tandem arrangement with center distance $H = 1.5D$ in uniform potential flow along positive $x$ -direction using ANSYS for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular-circular cylinder pair ( $N = 3, \gamma = 180^\circ$ and $h = 0.1$ ) (c) square -circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square -circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	107
Figure 4.45	Velocity contours around two-cylinders in tandem arrangement with center distance $H = 10d$ in uniform potential flow along positive $x$ -direction using complex potential function for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular -circular cylinder pair ( $N = 3, \gamma = 180^\circ$ and $h = 0.1$ ) (c) square -circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square -circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	108
Figure 4.46	Velocity contours around two-cylinders in tandem arrangement with center distance $H = 10d$ in uniform potential flow along positive $x$ -direction using ANSYS for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular -circular cylinder pair ( $N = 3, \gamma = 180^\circ$ and $h = 0.1$ ) (c) square -circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square -circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	109
Figure 4.47	Velocity contours around two-cylinders in side-by-side arrangement with center distance $H = 1.5d$ in uniform potential flow along positive $x$ -direction using complex potential function for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular -circular cylinder pair ( $N = 3, \gamma = 180^\circ$ and $h = 0.1$ ) (c) square-circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square -circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	110
Figure 4.48	Pressure contours around two-cylinders in side-by-side arrangement with center distance $H = 1.5 d$ in uniform potential flow along positive $x$ -direction using complex potential function for the cases of (a) circular-circular cylinder pair ( $N = \infty$ or $h = 0$ ) (b) triangular-circular cylinder pair ( $N = 3, \gamma = 180^\circ$ and $h = 0.1$ ) (c)	

	square-circular cylinder pair ( $N = 4, \gamma = 45^\circ$ and $h = 0.1$ ) (d) $45^\circ$ rotated square-circular cylinder pair ( $N = 4, \gamma = 0^\circ$ and $h = 0.1$ ).....	111
Figure 4.49	Flow parameters on the surface of triangular cylinder ( $N = 3, \gamma = 180^\circ$ and $h=0.15$ ), (a) velocity profile and (b) pressure co-efficient profile obtained using present method while interacting with circular cylinder at the center distances $H = 1.5D, 2D, 2.5D, 3D$ and $100D$ , (c) velocity profile and (d) pressure profile on single triangular cylinder place in uniform potential flow.....	112
Figure 4.50	Maximum velocity (left) and minimum pressure co-efficient (right) around polygonal-circular cylinder pair in tandem and side-by-side configuration for varying center distance $H/D$ between the cylinders in uniform potential flow. Continues line shows the results for side by side arrangement and dashed line shows the results for tandem arrangement of cylinders.....	113
Figure 4.51	Velocity distribution on the surface of triangular cylinder in triangular-circular cylinder pair ( $N = 3, \gamma = 180^\circ$ , and $h = 0.1$ ) for center $H/D = 1.5, 2.0, 2.5, 3.0, 5.0, 10$ and for angle of attack $\alpha = 0^\circ, 30^\circ, 45^\circ, 60^\circ, 90^\circ$ . Angle of attack is measured from positive $x$ -axis.....	113
Figure 4.52	Velocity distribution on the surface of square cylinder in square-circular cylinder pair ( $N = 4, \gamma = 45^\circ$ , and $h = 0.1$ ) for center $H/D = 1.5, 2.0, 2.5, 3.0, 5.0, 10$ and for angle of attack $\alpha = 0^\circ, 30^\circ, 45^\circ, 60^\circ, 90^\circ$ . Angel of attack is measured from positive $x$ -axis.....	114
Figure 4.53	Velocity distribution on the surface of square cylinder in $45^\circ$ rotated square-circular cylinder pair ( $N = 4, \gamma = 0^\circ$ , and $h = 0.1$ ) for center $H/D = 1.5, 2.0, 2.5, 3.0, 5.0, 10$ and for angle of attack $\alpha = 0^\circ, 30^\circ, 45^\circ, 60^\circ, 90^\circ$ . Angel of attack is measured from positive $x$ -axis.....	114
Figure 4.54	Pressure distribution on the surface of triangular cylinder in triangular-circular cylinder pair ( $N = 3, \gamma = 180^\circ$ , and $h = 0.1$ ) for center $H/D = 1.5, 2.0, 2.5, 3.0, 5.0, 10$ and for angle of attack $\alpha = 0^\circ, 30^\circ, 45^\circ, 60^\circ, 90^\circ$ . Angle of attack is measured from positive $x$ -axis.....	115
Figure 4.55	Pressure distribution on the surface of square cylinder in $45^\circ$ rotated square-circular cylinder pair ( $N = 4, \gamma = 45^\circ$ , and $h = 0.1$ ) for center $H/D =$	

	1.5, 2.0, 2.5, 3.0, 5.0, 10 and for angle of attack $\alpha = 0^{\circ}, 30^{\circ}, 45^{\circ}, 60^{\circ}, 90^{\circ}$ . Angle of attack is measured from positive $x$ -axis.....	115
Figure 4.56	Pressure distribution on the surface of square cylinder in 450 rotated square-circular cylinder pair ( $N = 4, \gamma = 0^{\circ}$ , and $h = 0.1$ ) for center $H/D = 1.5, 2.0, 2.5, 3.0, 5.0, 10$ and for angle of attack $\alpha = 0^{\circ}, 30^{\circ}, 45^{\circ}, 60^{\circ}, 90^{\circ}$ . Angle of attack is measured from positive $x$ -axis.....	116
Figure 4.57	Maximum velocity around polygonal-circular cylinder pair in uniform potential flow for angle of attack $\alpha = 0^{\circ}$ to $180^{\circ}$ measured from positive $x$ -axis. The distance between two-cylinders $H/D$ is varied from 1.5 to 10.....	118
Figure 4.58	Velocity (left) and Pressure (right) profile on the surface of triangular cylinder ( $N = 3, h = 0.15$ ) interacting with circular cylinder for the center distance $H = 1.5D$ and $\infty$ in uniform potential flow are shown for different flow angles $\alpha = 0^{\circ}, 30^{\circ}, 45^{\circ}, 60^{\circ}$ and $90^{\circ}$ . Flow angles are measured from positive $x$ -axis. Markers shows the locations of extremum values of flow parameters.....	119
Figure 4.59	Hydrodynamic force co-efficient on polygonal cylinders of corner radius $\rho = 1, 0.1$ and $0.01$ interacting with circular cylinder for varying center distance $H/D$ in uniform potential flow along the line connecting the centers of cylinders.....	121
Figure 4.60	Force co-efficient $C_{fx}$ on polygonal cylinder interacting with circular cylinder for different center distances $H/D = 1.5, 2, 2.5, 3, 5,$ and $10$ in uniform potential flow of varying angle of attack $\alpha = 0^{\circ}$ to $180^{\circ}$ , the angle of attack is measured from positive $x$ -axis. The corner radius of the polygonal shaped cylinders is considered $\rho = 0.2$ .....	122
Figure 4.61	Velocity ( $V/U$ ) and pressure co-efficient ( $C_p$ ) on the surface interacting triangular and square cylinder is shown for center distances $H = 4$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^{\circ}$ . The cylinder pair with same geometrical parameters is obtained in ANSYS using key points exported from MATLAB program of the present method.....	124
Figure 4.62	Pressure co-efficient ( $C_p$ ) on the surface of two interacting polygonal cylinders in triangular-triangular, triangular-diamond, and triangular -square cylinder pairs,	

	obtained for center distances $H = 3, 5$ , and $10$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^\circ$ .....	127
Figure 4.63	Pressure co-efficient ( $C_p$ ) on the surface of two interacting polygonal cylinders in diamond-triangular, diamond -diamond, and diamond-square cylinder pairs, obtained for center distances $H = 3, 5$ , and $10$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^\circ$ .....	127
Figure 4.64	Pressure co-efficient ( $C_p$ ) on the surface of two interacting polygonal cylinders in square-triangular, square -diamond, and square-square pairs, obtained for center distances $H = 3, 5$ , and $10$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^\circ$ .....	128
Figure 4.65	Velocity distribution on the surface of interacting polygonal cylinders in triangular-triangular, triangular -diamond, and triangular-square cylinder pairs for different center distances and the corner radii $\rho_1 = \rho_2 = 0.1$ .....	128
Figure 4.66	Velocity distribution on the surface of interacting polygonal cylinders in diamond-triangular, diamond -diamond, and diamond-square cylinder pairs for different center distances and the corner radii $\rho_1 = \rho_2 = 0.1$ .....	129
Figure 4.67	Velocity distribution on the surface of interacting polygonal cylinders in square-triangular, square -diamond, and square-square cylinder pairs for different center distances and the corner radii $\rho_1 = \rho_2 = 0.1$ .....	130
Figure 4.68	Velocity profile on the surface of diamond shaped cylinder ( $N_1 = 4, \rho_1 = 0.11, \gamma_1 = 0^\circ$ ) interacting with pentagonal cylinder ( $N_2 = 5, \rho_2 = 0.11, \gamma_2 = 180^\circ$ ) at center distance $H = 100$ obtained using present method is shown by continues solid line, and compared with the velocity profile on the surface of single diamond shaped cylinder of same geometrical parameters in uniform potential flow is shown by dotted line.....	131
Figure 4.69	Velocity profile on the surface of interacting polygonal cylinders in triangular-triangular, triangular -diamond, and triangular-square cylinder pairs for center distances $H = 5$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^\circ, 30^\circ, 45^\circ, 60^\circ$ and $90^\circ$ .....	132
Figure 4.70	Velocity profile on the surface of interacting polygonal cylinders in diamond-triangular, diamond -diamond, and diamond -square cylinder pairs for center	

	distances $H = 5$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^0, 30^0, 45^0, 60^0$ and $90^0$ .....	132
Figure 4.71	Velocity profile on the surface of interacting polygonal cylinders in square-triangular, square-diamond, and square-square cylinder pairs for center distances $H = 5$ , corner radii $\rho_1 = \rho_2 = 0.1$ , and flow angle $\alpha = 0^0, 30^0, 45^0, 60^0$ and $90^0$ .....	133
Figure 4.72	Minimum pressure co-efficient ( $Cp_{min}$ ) on the surface of interacting polygonal cylinders in triangular-triangular, triangular -diamond, triangular -square cylinder pairs for corner radii $\rho_1 = \rho_2 = 0.1$ , angle of attack $0^0 \leq \alpha \leq 180^0$ , and center distances $H = 3, 5, 7$ and $10$ .....	133
Figure 4.73	Minimum pressure co-efficient ( $Cp_{min}$ ) on the surface of interacting polygonal cylinders in diamond-triangular, diamond-diamond, diamond-square cylinder pairs for corner radii $\rho_1 = \rho_2 = 0.1$ , angle of attack $0^0 \leq \alpha \leq 180^0$ , and center distances $H = 3, 5, 7$ and $10$ .....	134
Figure 4.74	Minimum pressure co-efficient ( $Cp_{min}$ ) on the surface of interacting polygonal cylinders in square-triangular, square-diamond, square-square cylinder pairs for corner radii $\rho_1 = \rho_2 = 0.1$ , angle of attack $0^0 \leq \alpha \leq 180^0$ , and center distances $H = 3, 5, 7$ and $10$ .....	134
Figure 4.75	Velocities ( $V/U$ ) on the surface of interacting polygonal cylinders are investigated for corner radii $\rho_1 = \rho_2 = 0.1$ , flow angle $\alpha = 0^0$ , center distance $H = 3$ and orientation angles $\gamma_1 = \gamma_2 = 180^0, 150^0, 135^0, 120^0$ and $90^0$ .....	135
Figure 4.76	The effect of number of sides $N_2$ of polygonal cylinder ( $z_2$ ) on the velocity ( $V/U$ ) and pressure ( $Cp$ ) distribution for corner radii $\rho_1 = \rho_2 = 0.1$ , flow angle $\alpha = 0^0$ , center distances $H = 5$ and the orientation angles $\gamma_1 = \gamma_2 = 180^0$ .....	137
Figure 4.77	Velocity distribution on the surface of diamond shaped cylinder interacting with triangular cylinder for the center distance $H = 3$ , flow angle $\alpha = 0^0$ and, corner radii $\rho_1 = \rho_2 = 0.01, 0.05, 0.1, 0.3, 0.5, 0.8$ and $1$ .....	138
Figure 4.78	Hydrodynamic force ( $Cfx$ ) acting on polygonal cylinders during interaction for center distance $2.5 \leq H \leq 40$ , flow angle $\alpha = 0^0$ , corner radii $\rho_1 = \rho_2 = 0.01, 0.1$ and $1$ .....	141

Figure 4.79 Effect of flow angle ( $0^0 \leq \alpha \leq 180^0$ ) on hydrodynamic force ( $C_{fx}$ ) acting on cylinders in triangular-triangular, triangular-diamond, triangular-square cylinder pairs for center distance  $H = 3, 4, 5, 6,$  and  $10,$  and corner radii  $\rho_1 = \rho_2 = 0.1 \dots$  142

Figure 4.80 Effect of flow angle ( $0^0 \leq \alpha \leq 180^0$ ) on hydrodynamic force ( $C_{fx}$ ) acting on cylinders in diamond-triangular, diamond-diamond, diamond-square cylinder pairs for center distance  $H = 3, 4, 5, 6,$  and  $10,$  and corner radii  $\rho_1 = \rho_2 = 0.1 \dots$  143

Figure 4.81 Effect of flow angle ( $0^0 \leq \alpha \leq 180^0$ ) on hydrodynamic force ( $C_{fx}$ ) acting on cylinders in square-triangular, square-diamond, square-square cylinder pairs for center distance  $H = 3, 4, 5, 6,$  and  $10,$  and corner radii  $\rho_1 = \rho_2 = 0.1 \dots$  143

Figure C.1 Bilinear mapping from the annular area ( $q \leq \zeta \leq 1$ ) from  $\zeta$ -plane to infinite region with two non-overlapping unit circles  $\xi_1$  and  $\xi_2$  at distance  $H$  apart in  $\xi$ -plane. Point  $B$  on the positive real axis in  $\zeta$ -plane is transformed to point  $B'$  on the real axis in  $\xi$ -plane..... 169