

# List of Figures

|      |   |    |
|------|---|----|
| 1.1  | Correlation between critical parameters for metallic glass production | 2  |
| 1.2  | Overview of different Glass-forming ability measures . . . . .        | 4  |
| 2.1  | VAF for LJ system at $T = 1.5$ and $\rho = 0.2$ . . . . .             | 24 |
| 2.2  | VAF for LJ system at $T = 1.5$ and $\rho = 0.4$ . . . . .             | 24 |
| 2.3  | VAF for LJ systems at $T = 1.5$ and $\rho = 0.84$ . . . . .           | 25 |
| 2.4  | Residue plots showing comparison of the quality of VAFs . . . . .     | 27 |
| 2.5  | VAF for liquid lithium at 725 K. . . . .                              | 28 |
| 2.6  | VAF for liquid lithium at 574 K . . . . .                             | 28 |
| 2.7  | VAF for liquid lithium at 470 K . . . . .                             | 29 |
| 2.8  | VAF for liquid Na at 900 K . . . . .                                  | 29 |
| 2.9  | VAF for liquid Na at 380 K . . . . .                                  | 30 |
| 2.10 | VAF for liquid potassium at 450 K . . . . .                           | 30 |
| 2.11 | VAF for liquid Cu at 1873 K . . . . .                                 | 31 |
| 2.12 | VAF for liquid Cu at 1773 K . . . . .                                 | 31 |
| 2.13 | VAF for liquid Cu at 1573 K . . . . .                                 | 32 |
| 2.14 | VAF for liquid Cu at 1423 K . . . . .                                 | 32 |
| 2.15 | VAF for liquid Ni at 1923 K . . . . .                                 | 33 |
| 2.16 | VAF for liquid Ni at 1810 K . . . . .                                 | 33 |
| 2.17 | VAF for liquid Ni at 1735 K . . . . .                                 | 34 |
| 2.18 | VAF for liquid Ni at 1500 K . . . . .                                 | 34 |
| 2.19 | VAF for liquid Fe at 2023 K . . . . .                                 | 35 |
| 2.20 | VAF for liquid Fe at 1923 K . . . . .                                 | 35 |

|      |  |    |
|------|--|----|
| 2.21 | VAF for liquid Fe at 1873 K . . . . .  | 36 |
| 2.22 | VAF for liquid Fe at 1833 K . . . . .  | 36 |
| 2.23 | Variation of Meijer G-function . . . . .   | 47 |
| 2.24 | VAFs for LJ systems at $T = 1.5$ with different densities . . . . .  | 48 |
| 3.1  | Excess entropy and configuration entropy in $\text{Cu}_x\text{Zr}_{100-x}$ alloys . . . . .                                  | 59 |
| 3.2  | Mismatch entropy and $\Delta S^E / Nk_B$ in $\text{Cu}_x\text{Zr}_{100-x}$ alloys . . . . .                                  | 59 |
| 3.3  | Atomic packing efficiency in various Voronoi polyhedra types in $\text{Cu}_{50}\text{Zr}_{50-x}\text{Al}_x$ alloys . . . . . | 60 |
| 3.4  | Excess entropy and configurational entropy in $\text{Cu}_{50}\text{Zr}_{50-x}\text{Al}_x$ alloys . . . . .                   | 62 |
| 3.5  | Mismatch entropy and $\Delta S^E / Nk_B$ in $\text{Cu}_{50}\text{Zr}_{50-x}\text{Al}_x$ alloys . . . . .                     | 63 |
| 4.1  | Gibbs free energy difference $\Delta G$ for $\text{Zr}_{56}\text{Co}_{28}\text{Al}_{16}\text{Y}_0$ . . . . .                 | 71 |
| 4.2  | Gibbs free energy difference $\Delta G$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_2$ . . . . .                 | 71 |
| 4.3  | Gibbs free energy difference $\Delta G$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_7$ . . . . .                 | 72 |
| 4.4  | Gibbs free energy difference $\Delta G$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_{10}$ . . . . .              | 72 |
| 4.5  | Specific heat capacity difference $\Delta C_p$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_0$ . . . . .          | 74 |
| 4.6  | Specific heat capacity difference $\Delta C_p$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_2$ . . . . .          | 74 |
| 4.7  | Specific heat capacity difference $\Delta C_p$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_7$ . . . . .          | 75 |
| 4.8  | Specific heat capacity difference $\Delta C_p$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_{10}$ . . . . .       | 75 |
| 4.9  | Enthalpy difference $\Delta H$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_0$ . . . . .                          | 77 |
| 4.10 | Enthalpy difference $\Delta H$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_2$ . . . . .                          | 77 |
| 4.11 | Enthalpy difference $\Delta H$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_7$ . . . . .                          | 78 |
| 4.12 | Enthalpy difference $\Delta H$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_{10}$ . . . . .                       | 78 |
| 4.13 | Entropy difference $\Delta S$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_0$ . . . . .                           | 79 |
| 4.14 | Entropy difference $\Delta S$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_2$ . . . . .                           | 79 |
| 4.15 | Entropy difference $\Delta S$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_7$ . . . . .                           | 80 |
| 4.16 | Entropy difference $\Delta S$ for $\text{Zr}_{54}\text{Co}_{28}\text{Al}_{16}\text{Y}_{10}$ . . . . .                        | 80 |
| 5.1  | DSC thermograms for ZBLAN glass at four different heating rates. . . . .   | 86 |

|     |  |    |
|-----|--|----|
| 5.2 | Kissinger plot for ZBLAN glass . . . . .     | 87 |
| 5.3 | Augis-Bennett plot for ZBLAN glass . . . . . | 88 |